

CUTTING PLOTTER

Mimaki™

Product Brochure

CG-SR III Series

CG-60/100/130SR III

Extreme curve
cutting speed




High Productivity

Up to 2 times the curve cutting speed*

The production speed of complicated cutting tasks has improved greatly.

* Compared with CG-SRII series



Accurate Contour Cutting

Ideal for creating seals


“Continuous Crop Mark Detection” enables the continuous contour cutting of nested data. The new “Segment Correction Function”, which detects intermediate crop marks, enables accurate contour cutting of long-length prints. Furthermore, the original “Half Cut Function” enables easy removal of the nested data.



Remote Monitoring

Event Notification Function

Events, such as completion of cutting and error occurrence, are sent to a preset e-mail address. Monitoring the state of machine is unnecessary, enabling unattended operation.



CUTTING PLOTTER

CG-SR III Series

CG-60/100/130SR III

Affordably priced but technologically advanced. Achieve the highest return on your investment.

Wider Application Possibilities

the range of materials for various applications is increased.

Clamp pressure can be switched in two levels in order to cover a wide range of sheets including thick materials.

The optional sheet basket enables stable long-length cutting.

Two dedicated software are provided as standard

for CorelDRAW[®] Simple Cut

for CorelDRAW[®] Simple Cut


1MVH JO DVUUJOH TPGUXBSF GPS 'E' POUT UFNQMBUFT BOE EFDPSBUFE
 DSFBUFF DPOUPVS DVUUJOH EBUB GSPN JNBLJ T XFCTJUF 'E' PPSBMMSTU BSHPSF JOTUBMMFE UP
 BOE QFSGPSNT TQMJU DVUUJOH XUJULIMJOH GVOUJPO DSBUFF 101 JUFNT BOE TJHOT
 GPS IJHIFS DVUUJOH OFFET

User-friendly with Various functions

Continuous Crop Mark Detection


Crop marks are automatically and continuously detected. Printed graphics are accurately contour cut due to the compensation for image distortion. The detection of a maximum of 4 crop marks provides a precision finish.

Nested data which is continuously arranged in the directions of X-axis and Y-axis is cut by automatically making corrections.




Half Cut Function

Cutting printed graphics while leaving a few joints make it possible to cut figures, designs from substrates with backing sheets, fold lines for POP, and many other applications.



Segment Compensation

Intermediate crop marks of the feed direction are detected, enabling four-point corrections for each segment. This leads to accurate, long-length cutting, even if the image is distorted.



User Upgrade of Firmware

A tool for keeping the firmware up-to-date is provided. The upgrade can be done quickly and easily by the user, thus ensuring the firmware is in the latest condition.

Other Functions

- Division Cut Function** Division cut of data larger than sheet width.
- Overcut Function** Minimize uncut portions by overlapping the starting and ending point.
- Larger LCD** 3-inch LCD (liquid crystal display) ensures easy operation.
- Ethernet Connection** Network control via integration into office LAN.

Specifications

Item	CG-60SRIII	CG-100SRIII	CG-130SRIII
Acceptable sheet width	90~740 mm (3.5~29.1")	90~1,250 mm (3.5~49.2")	90~1,550 mm (3.5~61.0")
Effective cutting area	606mm51M(23.9' 167.3')	1,070mm51M(42.1' 167.3')	1,370mm51M(53.9' 167.3')
Maximum speed	Cutting: 70 cm/s, Moving: 100 cm/s		
Adjustable speed range	1 - 10 cm/s(1 cm/s step adjustment) 1 - 70 cm/s(5cm/s step adjustment)	0.4 - 3.9/s(0.4"/s step adjustment) 0.4 - 27.8/s(2.0"/s step adjustment)	
Mechanical resolution	X direction: 2.5 μm, Y direction: 5 μm		
Command resolution	25 μm or 10 μm (MGL-IIC) / 100 μm, 50 μm (MGL-Ic1)		
Repeatability*1	± 0.2 mm / 2 M		
Effective Repeatability*2	586 mm × 2 M	1,050 mm × 2M	1,350 mm × 2M
Maximum pressure	500g		
Range of down pressure	Cutter: 10 - 20 g (2 g step), 20 - 100 g (5 g step), 100 - 500g (10g step) Pen: 10 - 20 g (2 g step), 20 - 100 g (5 g step), 100 - 150g (10 g step)		
Acceptable sheet*2	Vinyl sheet, Fluorescent type vinyl sheet, Reflective sheet, Rubber sheet		
Acceptable tool*3	Cutter, Ball-point pen		
Type of command	MGL-IIC / MGL-Ic1		
Interface	USB2.0, RS-232C, Ethernet		
Receiver buffer size	27 MB Standard (When sorting, 17 MB)		
Operational environment	5 - 35 degC (41 - 95 degF), 35 - 75% (RH), Non-condensation		
Power requirement	AC 100 V - 240 V, 145 VA or less		
Dimensions (W x D x H)	1,030 430 335mm (40.6" 16.9" 13.2") 1,030 430 1,185mm*4 (40.6" 16.9" 46.7")*4	1,530 580 1,150mm (60.2" 22.8" 45.3")	1,830 580 1,150mm (72.0" 22.8" 45.3")
Weight	24kg (52.9lb.)	41kg (90.4lb.)	46kg (101.4lb.)
Stand	Optional equipment	Standard equipment	Standard equipment

*1 Except for media expansion and contraction due to temperature.
 *2 Operated with Mimaki specified media, cutter and cutting conditions. Thickness of rubber and its cutting speed are limited.
 *3 Guaranteed accuracy environment: Temperature 12-25 degC (53.6 - 77 degF) Humidity 45-65%
 *4 When equipped with the optional stand (OPT-0231)

Supplies & Options

Item	Quantity	Item-No
Standard blade for vinyl	3	SPB-0030
Blade for vinyl	3	SPB-0001
Blade for small character	3	SPB-0003
Blade for reflective sheet	2	SPB-0006
Blade for fluorescent sheet	3	SPB-0007
Blaabe set(rubber sheet)	3	SPB-0084
Cutter holder	1	SPA-0090
Pen adaptor	1	SPA-0169
Refill type pen adaptor	1	SPA-0183
Refill lead for Mitsubishi ball-point pen	10	SPC-0726
Stand for CG-60	1	OPT-C0235
Sheet basket 60	1	OPT-C0234
Sheet basket 100	1	OPT-C0232
Sheet basket 130	1	OPT-C0233
Roll shaft 100	1	OPT-C0223
Roll shaft 130	1	OPT-C0224

CG-60SRIII	CG-100SRIII	CG-130SRIII
Stand and sheet basket of CG-60SRIII are optional.		
Sheet baskets of CG-100SRIII and CG-130SRIII are optional.		

Mimaki MIMAKI ENGINEERING CO., LTD.
 2182-3 Shigeno-otsu, Tomi-city, Nagano 389-0512, Japan
 mimaki.com Tel: .

Mimaki Global Network

64" 64" */\$ &VSPQF # 6301 & # 7
 #SB[JM # 3*4* - \$0. &3\$*0 & .1.1035*\$*0 -5% *OEPOFTJBS */%0/&4**
 *OEJB */% ** 13*7*5& - . . *5&% "VTUSBMJB. "6453"-* 15: -5%
 5BJXB /*/*&&3*/(5**8*/ \$0 -5% \$IJOB 4)"/()* 53%*/(\$0 -5%
 4JOHBQPSF. 4*/(103& 15& -5% 5IBJMBOE 5)**-/% \$0 -5%