

Product Name: Pigment Ink Orange MSDS No.031-34W01OC First issue: Apr 10, 2008 Revised: Sep 09, 2018 Page 1 of 6

Material Safety Data Sheets Considered a hazardous substance according to OSHA 29 CFR 1910.1200.

1. Product and Company Identification

Product Name	: Pigment Ink Orange	
Product Code	: SPC-0180O	
General Use	: Ink jet printing ink	
Product Description	: Pigment ink	
MSDS Number	:031-34W01OC	
Manufacture		
Company Name	: Mimaki Engineering Co., Ltd	
Address	2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan	
Telephone No.	: +81-268-64-2413	
Importer/Distributor Established in USA		
Company Name	: MIMAKI USA. INC.	
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A	
Telephone No.	: 1-678-730-0170	
Emergency Telephone No.	: +81-268-64-2413	

2. Hazards Identification

Emergency Overview	: Ink component is a Orange liquid that cause eye, nose or throat
	irritation, and that effects anesthesia, if inhales.
	Ink may flash, when under high temperature.
	Avoid contact with eyes or clothing.
	In the case of skin contact, wash with soap and water.
	Keep out of reach of children.
	This product is not classified.
Potential Health Effects	
Inhalation	: Intentional exposure to ink vapors (mist) will cause respiratory
	irritation and anesthesia.
Eye Contact	: Ink contact with eye will be irritating.
Skin Contact	: Ink contact with skin may cause minimally irritation.
Ingestion	: May cause upset stomach.
Carcinogens	: None known.
Potential Environmental	: Not available.
Effects	



Product Name: Pigment Ink Orange MSDS No.031-34W01OC First issue: Apr 10, 2008 Revised: Sep 09, 2018 Page 2 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

3. Composition / Information On Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Glycerols	About 20	Trade Secret	Trade Secret
2	Proprietary organic materials	10-15	Trade Secret	Trade Secret
3	Proprietary dyes and pigmenta	5-10	Trade Secret	Trade Secret
4	Diethylene glycol	About 5	111-46-6	$C_4H_{10}O_3$
5	TEGBE	<5	143-22-6	$C_{10}H_{22}O_4$
6	Water	balance	7732-18-5	H_2O

4. First Aid Measures

Inhalation	: Remove subject to ventilated fresh air. Consult physician if	
	necessary.	
Eye Contact	: Immediately flush with room temperature, low pressure, and clean	
	water for at least 15 minutes. Seek medical attention if eye	
	irritation continues.	
Skin Contact	: Wash surface areas with soap and water. Wash soiled clothing before	
	rewearing. Consult a physician if irritation continues.	
Ingestion	: Seek medical advice; and attention if stomach continues to be upset.	
Protection To First-Aiders	: Not available.	

5. Fire Fighting Measures

Flammable Properties	: Not flammable.
Extinguishing Media	: Dry chemical or carbon dioxide.
Fire Fighting	: No special fire fighting procedures are required other than
Instructions	breathing apparatus. No special explosion hazards are known.

6. Accidental Release Measures

Personal Precautions	: No eye or skin protection required during clean-up. Use proper
	ventilation.
Land Spill	: If a spill occurs, use sponges to wipe-up ink, and then rinse with



Product Name: Pigment Ink Orange MSDS No.031-34W01OC First issue: Apr 10, 2008 Revised: Sep 09, 2018 Page 3 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

	damp cloth. Place waste in closed container for disposal.
Water Spill	: Do not dispose of waste to the sewer.
7. Handling And Storage	
Handling	: Keep out of reach of children and do not drink ink.
	Do not dismantle cartridge.
	Make sure cartridge is dry before insertion into printer housing.
Storage	: Do not store the cartridge in high or freezing temperatures.
	Keep cartridge out of direct sunlight.
	Do not store cartridges with oxidizing agents or explosives.

8. Exposure Controls / Personal Protection

Exposure Limit Values : Not available.

Exposure Controls

Occupational Exposure Controls

Engineering Controls	: Not special	measures required.
----------------------	---------------	--------------------

Personal Protection

Respiratory	: Not required under suitable use as setting the cartridge on the
Protection	printer; however, self-contained breathing apparatus or organic
	canister mask is sufficient when used for work.

Hand Protection : Not required under suitable use as setting the cartridge on the printer; however, wearing gloves is sufficient.



Eye Protection : Not required under suitable use as setting the cartridge on the printer; however, wearing safety goggles is sufficient.



Skin Protection : Not required under suitable use as setting the cartridge on the printer; however, wearing gloves is sufficient.



Product Name: Pigment Ink Orange MSDS No.031-34W01OC First issue: Apr 10, 2008 Revised: Sep 09, 2018 Page 4 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.



Environmental Exposure Controls

: Not established.

9. Physical And Chemical Properties

Appearance - Physical state	: liquid	
- Colour	: Orange	
Odour	: None	
pH	: 8.0-10.5 (20 degree C)	
Boiling Point / Boiling Range	: Not available.	
Melting Point / Merting Range	: Not available.	
Flash Point	: Not detected until 95 degree C	
	(closed cup, ASTM D3278)	
Flammability(solid, gas)	: Not available.	
Relative density	: 1.00-1.10 (20 degree C)	
Solubility	: Not available.	
Water solubility	: Complete	
Viscosity	: 3.5-4.5 (20 degree C)	
VOC	: 100 g/l	

10. Stability And Reactivity

Conditions To Avoid	: High and freezing temperatures.
Stability	Stable under temperature.
Materials To Avoid	: Oxidizers and explosives
Hazardous Reactions/	: None
Decomposition Products	

11. Toxicologocal Information

Acute Toxicity

Oral LD₅₀ No data available Dermal LD₅₀ No data available Inhalant LC₅₀ No data available.



Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Eye Irritation	: Overexposure of eye surface to ink may be mildly irritating.
Skin Irritation	: Overexposure of skin to ink contact may cause irritation and in some
	people swelling and redness.
Sensitization	: Not available
Mutagenicity	: None known.
Carcinogenicity	: None known.

12. Ecological Information

Ecotoxicity	: No data available on the adverse effects of this ink on $$	the		
	environment.			
Persistence And	: No data available on the adverse effects of this ink on	the		
Degradability	environment.			
Bioaccumulative	: No data available on the adverse effects of this ink on \cdot	the		
Potential	environment.			
Other Adverse Effects	: No data available.			

13. Disposal Considerations

Disposal should be in accordance with federal, state, and local requirements. Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information

UN Class/UN Number : Not applocable. DOT, IMO, or IATA : Not hazardous classification

15. Regulatory Information

TSCA Section 4(a) Final: Not regulated.Test Rules Regulated: Not regulated.TSCA Section 8(a): Not regulated.Preliminary Assessment: Information Rule(PAIR)TSCA Section12(b): Not regulated.



Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

One-Time Export Notification Regulated California Proposition 65

: WARNING:



This product can expose you to chemicals including Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and dose not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

Revision history

Version	Date	Content
1.0	Apr 10, 2008	First issue.
2.0	Sep 09, 2018	Proposition65 Information Described