

MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 1 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : Reactive Dye Ink Rc210 Ligth Cyan

Product Code : SPC-0702LC-1
General Use : Ink Jet Ink
Product Description : Ink Jet Ink
MSDS Number : 031-36W193P

Manufacture

Company Name : Mimaki Engineering Co., Ltd

Address : 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan

Telephone No. : +81-268-64-2413

Importer/Distributor Established in USA

Company Name : MIMAKI USA. INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A

Telephone No. : +1-678-730-0170 Emergency Telephone No. : +81-268-64-2281

2. HAZARDS IDENTIFICATION

WARNING!

Emergency Overview

Irritating to eyes

May be harmful if swallowed, inhaled, or absorbed through skin

Mist or aerosol may be irritating to eyes, nose, throat, and lungs

May cause central nervous system depression

Appearance Blue Physical State Liquid. Odor Specific

Potential Health Effects

Principle Routes of Exposure Inhalation. Skin contact. Eye contact.

Acute Toxicity

Eyes Irritating to eyes.



MSDS No. 031-36W193P First issue: 2011/01/26

Revised: 2018/08/31 Page 2 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Skin May cause irritation. May be harmful if absorbed through skin.

Inhalation May be harmful if inhaled. Inhalation of aerosols: May cause irritation of respiratory

tract. May cause central nervous system depression with nausea, headache,

dizziness, vomiting, and incoordination.

Ingestion May be harmful if swallowed. May cause adverse liver effects. May cause adverse

kidney effects. May cause additional affects as listed under "Inhalation".

Chronic Effects May cause adverse liver and kidney effects. May cause central nervous system

depression. Contains materials which based on animal tests may cause adverse

reproductive and birth effects at maternally toxic levels.

Main Symptoms Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting.

Aggravated Medical Central nervous system. Pre-existing eye disorders. Respiratory disorders.

Conditions

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Water	7732-18-5	40-50
Diglycerin	59113-36-9	20-30
Ethylene glycol	107-21-1	15-25
Reactive Dye	Trade Secret	1-10
Additives	Trade Secret	<5



MSDS No. 031-36W193P First issue: 2011/01/26

Revised: 2018/08/31 Page 3 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Keep eye wide open while

rinsing. If symptoms persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water. If symptoms persist, call a

physician.

Inhalation IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

breathing. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Call a physician or Poison Control Center immediately. Clean mouth with water

and afterwards drink plenty of water. Do not induce vomiting without medical

advice.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Combustible material: may burn but does not ignite readily.

Flash Point Not determined.

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Explosion Data

Sensitivity to Mechanical Impact None
Sensitivity to Static Discharge None



MSDS No. 031-36W193P First issue: 2011/01/26

Revised: 2018/08/31 Page 4 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Protective Equipment andAs in any fire, wear self-contained breathing apparatus pressure-demand,

Precautions for Firefighters MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Health Hazard 2 Flammability 1 Instability 0 Physical and Chemical

Hazards -

HMIS Health Hazard 2* Flammability 1 Physical Hazard 0 Personal Protection -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Wear protective gloves/clothing and eye/face protection. Ensure adequate

ventilation. Avoid contact with the skin and the eyes.

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. Do not flush

into surface water or sanitary sewer system.

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up For spills: Absorb with inert absorbent materials such as: Dry sand. Vermiculite.

Activated charcoal. Place in appropriate chemical waste container.

7. HANDLING AND STORAGE

Handling Handle in accordance with good industrial hygiene and safety practice. Wear

personal protective equipment. Avoid breathing vapors or mists. Avoid contact with

skin, eyes and clothing.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

^{*}Indicates a chronic health hazard.



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 5 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene glycol	Ceiling: 100 mg/m³ aerosol only	(vacated) Ceiling: 50 ppm	-
107-21-1		(vacated) Ceiling: 125 mg/m ³	

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965

F.2d 962 (11th Cir., 1992).

Engineering Measures Showers

Eyewash stations Ventilation systems

Personal Protective Equipment

Eye/Face ProtectionSafety glasses with side-shields.Skin and Body ProtectionWear protective gloves/clothing.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Positive-pressure supplied air

respirators may be required for high airborne contaminant concentrations.

Respiratory protection must be provided in accordance with current local

regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 6 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceBlue.OdorSpecific.Odor ThresholdNo information available.Physical StateLiquid

pH No information available.

Flash Point No information available. Autoignition Temperature No information available.

Decomposition Temperature No information available. Boiling Point/Range No information available

Melting Point/Range No information available

Flammability Limits in Air No information available. Explosion Limits No information available.

Solubility No information available Evaporation Rate No information available

Vapor Pressure No data available Vapor Density No data available

VOC Content (%) 15-25

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products Strong oxidizing agents. Chlorosulfonic acid, oleum, sulfuric acid, perchloric acid,

chromium trioxide, potassium permanganate and sodium peroxide.

Conditions to Avoid Heat, flames and sparks.

Hazardous Decomposition Products Sulfur oxides. Nitrogen oxides (NOx). Carbon dioxide (CO2) Carbon monoxide

(CO).

Hazardous Polymerization Hazardous polymerization does not occur.



MSDS No. 031-36W193P First issue: 2011/01/26

Revised: 2018/08/31 Page 7 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information May be harmful by inhalation, ingestion, or skin absorption. Irritating to eyes: Mist

or aerosol may be irritating to eyes, nose, throat, and lungs.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol	4000 mg/kg (Rat)	9530 μL/kg (Rabbit)	-

Chronic Toxicity

Chronic Toxicity May cause adverse liver and kidney effects. May cause central nervous system

depression. Contains materials which based on animal tests may cause adverse

reproductive and birth effects at maternally toxic levels.

Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

Target Organ Effects Central nervous system (CNS). Liver, kidney, and respiratory system. Reproductive

system. Contains material that may adversely affect the developing fetus.



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 8 of 12

Material Safety Data Sheets CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna (Water
			Microorganisms	Flea)
Ethylene glycol	EC50: 6500 - 13000 mg/L	LC50: 41000 mg/L	EC50 = 10000 mg/L 16 h	EC50: 46300 mg/L
	Pseudokirchneriella	Oncorhynchus mykiss 96 h	EC50 = 620 mg/L 30 min	Daphnia magna 48 h
	subcapitata 96 h	LC50: 14-18 ml/L	EC50 = 620.0 mg/L 30 min	
		Oncorhynchus mykiss 96 h		
		static		
		LC50: 27540 mg/L Lepomis		
		macrochirus 96 h static		
		LC50: 40761 mg/L		
		Oncorhynchus mykiss 96 h		
		static		
		LC50: 40000-60000 mg/L		
		Pimephales promelas 96 h		
		static		
		LC50: 16000 mg/L Poecilia		
		reticulata 96 h static		

Chemical Name	Log Pow
Ethylene glycol	-1.93



MSDS No. 031-36W193P First issue: 2011/01/26

Revised: 2018/08/31 Page 9 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal

regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for

additional requirements.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 10 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

15. REGULATORY INFORMATION

International Inventories

TSCA All components are listed on the TSCA Inventory.

DSL All components are listed either on the DSL or NDSL.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylene glycol	107-21-1	15-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 11 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylene glycol	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

: WARNING:



This product can expose you to chemicals including Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Ethylene glycol	x	X	X	X	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Ethylene glycol		Mexico: Ceiling= 100 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials



MSDS No. 031-36W193P First issue: 2011/01/26 Revised: 2018/08/31

Page 12 of 12

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.



Chemical Name	NPRI
Ethylene glycol	X

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

Revision history

Version	Date	Content
1.0	2011/01/26	First Issue
2.0	2018/08/31	Sectiom15: Proposition65 Information Described