

Light Magenta

Page 1 of 6

MSDS No.031-37W202C First issue: Jun 1, 2011

Revised: Aug 30, 2018

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

1. Product and Company Identification

Product Name : Dye Sublimation Ink Sb52 Light Magenta

Product Code : SPC-0584LM-2, SPC-585LM-2

General Use : Ink jet printing ink
Product Description : Sublimation Ink
MSDS Number :031-37W202C

Manufacture

Company Name : Mimaki Engineering Co., Ltd

Address : 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan

Telephone No. : +81-268-64-2413

Importer/Distributor Established in USA

Company Name : MIMAKI USA. INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A

Telephone No. : 1-678-730-0170 Emergency Telephone No. : +81-268-64-2413

2. Hazards Identification

Emergency Overview : May cause skin sensitization with allergic skin rashes.

Avoid contact with eyes or clothing. In the case of skin contact, wash

with soap and water. Keep out of reach of children.

Potential Health Effects

Inhalation : Intentional exposure to ink vapors may cause respiratory irritation.

Eye Contact : Ink contact with eye may be irritation.

Skin Contact : Ink contact with skin may cause irritation, swelling, or redness.

Ingestion : May cause upset stomach.

Carcinogens : No ingredients are listed by OSHA, IARC, or NTP as known or

suspected carcinogens.

Potential Environmental

: Not available.

Effects



Light Magenta

MSDS No.031-37W202C First issue: Jun 1, 2011

Revised: Aug 30, 2018 Page 2 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

3. Composition / Information On Ingredients

No	Chemical Name	Wt%	CACNo	Chemical	
			CAS No.	Formula	
1	Disperse dye	Trade Secret	Trade Secret	Trade Secret	
2	Glycerols	Trade Secret	Trade Secret	Trade Secret	
3	Organic materials	<5	1336-21-6	NH ₄ OH	
4	Triethanolamine	<5	102-71-6	$\mathrm{C_6H_{15}NO_3}$	
5	Water	balance	7732-18-5	$_{ m H_2O}$	

4. First Aid Measures

Inhalation : If difficulties occur after vapour/aerosol has been inhaled, remove to

fresh air and seek medical attention.

Eye Contact : Wash affected eyes for at least 15 minutes under running water with

eyelids held open.

Skin Contact : Wash thoroughly with soap and water.

Ingestion : Rinse mouth and then drink plenty of water.

Protection To First-Aiders : Not available.

5. Fire Fighting Measures

Flammable Properties : Not flammable.

Extinguishing Media : water spray, dry extinguishing media, foam, carbon dioxide

Fire Fighting : Wear full fire-fighting turn-out gear (full bunker gear) and

Instructions respiratory protection (self-contained breathing apparatus).

6. Accidental Release Measures

Personal Precautions : Wear appropriate personal protective equipment.

Cleaning up Methods : Avoid release to the environment.

Absorb spillage with an inert material, then place in a chemical waste container for later safe disposal. Earth may be shoveled to



Light Magenta

MSDS No.031-37W202C

First issue: Jun 1, 2011 Revised: Aug 30, 2018

Material Safety Data Sheets

Page 3 of 6

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

contain spillage and to avoid contamination of sewers and water cources.

7. Handling And Storage

Handling : Do not breathe (dust, vapor, mist, gas).

Avoid contact with skin, eyes, or clothing.

Wash thoroughly after handling.

Destroy contaminated shoes in proper manner.

Storage : Keep container tightly closed and in a cool place.

Protect from temperatures below: 0 degree C. Protect from temperatures above: 40 degree C.

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name		TWA	STEL	Ceiling	Skin	SEN
1	Triethanolamine	ACGIH TLV	5mg/m3	N.E	N.E	N.E	N.E

Exposure Controls

Occupational Exposure Controls

Engineering Controls : It is better to place local exhaust equipment.

Personal Protection

Respiratory : Wear respiratory protection if ventilation is inadequate. Breathing

Protection protection if breathable aerosols/dust are formed.



Hand Protection : Chemical resistant protective gloves.



Eye Protection : Tightly fitting safety goggles(chemical goggles).



Light Magenta

MSDS No.031-37W202C

First issue: Jun 1, 2011 Revised: Aug 30, 2018

Material Safety Data Sheets

Page 4 of 6

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.



Skin Protection : To prevent ANY contact, wear impervious clothing such as gloves,

apron, boots, or whole body suits made from neoprene, as appropriate.









Environmental Exposure Controls

: Not available.

9. Physical And Chemical Properties

Appearance - Physical state : liquid

- Colour : Red

Odour : product specific

pH : 7.0~9.5

Boiling Point / Boiling Range : 100 degree C Water

Melting Point / Merting Range : Not available.

Flash Point : Not applicable.

Flammability(solid, gas) : Not available.

Specific Gravity : 1.00~1.20

Solubility : Not available.

Water solubility : complete

Viscosity : 3.0~5.0mPa.s(20 degree C)

10. Stability And Reactivity

Conditions To Avoid : High and freezing temperatures.

Stability : Stable

Materials To Avoid : Not available.

Hazardous Reactions/ : No hazardous decomposition products if stored and handled as

Decomposition Products prescribed/indicated.



Light Magenta

MSDS No.031-37W202C First issue: Jun 1, 2011

Revised: Aug 30, 2018

Material Safety Data Sheets

Page 5 of 6

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

11. Toxicologocal Information

Acute Toxicity : Not available.

Eye Irritation : May cause eye irritation.
Skin Irritation : May cause skin irritation.

Sensitization : Not available.

Mutagenicity : Not available.

12. Ecological Information

Ecotoxicity : Not available
Persistence And : Not available.

Degradability

Bioaccumulative : Not available.

Potential

Other Adverse Effects : Not available.

13. Disposal Considerations

: Must be dumped or incinerated in accordance with local regulations.

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information

Not classified as a dangerous good under transport regulations.

(USDOT / IMDG / IATA / ICAO)



Light Magenta

MSDS No.031-37W202C First issue: Jun 1, 2011

Revised: Aug 30, 2018 Page 6 of 6

Material Safety Data Sheets

CONSIDERED A HAZARDOUS SUBSTANCE ACCORDING TO OSHA 29 CFR 1910.1200.

15. Regulatory Information

OSHA Status : Not hazardous.
TSCA Status : released / listed

SARA TitleIII

Section 311/312 : Not hazardous.

(40 CFR 370)

California Proposition : WARNING:

65

This product can expose you to chemicals including

Diethanolamine, Ethylene glycol, α -Methyl styrene, which are known to the State of California to cause cancer/ birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and dose not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

Revision history

Version	Date	Content
1.0	Jun 1, 2011	First issue.
2.0	Aug 30, 2018	Section15: Proposition65 Information Described