

## 1. Product and Company Identification

Product Name	: Latex ink LX100 Magenta	
Product Code	: LX100-M-60-2	
General Use	: Ink for ink jet printer	
Product Description	: Aqueous ink	
MSDS Number	: 031-37W28MP	
Manufacture		
Company Name	: Mimaki Engineering Co., Ltd	
Address	: 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan	
Telephone No.	: +81-268-64-2413	
Importer / Distributor Established in USA		
Company Name	: MIMAKI USA. INC.	
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A	
Telephone No.	: 1-678-730-0100	
Emergency Telephone No.	: +81-268-64-2413	

## 2. Hazards Identification

[GHS Classification]	
Physical Hazards	
Out of classification or No classification	
Health Hazards	
Skin Corrosion / Irritation	: Category 3
Eye Damage / Irritation	: Category 2A
Toxic to Reproduction	Category 2

Environmental Hazards Out of classification or No classification

[GHS Label Elements]





Signal Word

Warning

# Hazard Statements

- H316 Causes mild skin irritation.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.

**Precautionary Statements** 

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

[Response]

P308 + P313 If exposed or concerned: Get medical advice/attention.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

 $\mathrm{P305}+\mathrm{P351}+\mathrm{P338}$  IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

[Disposal]

P501 Dispose of contents / container in accordance with local / regional / national / international regulation.

# 3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Diethylene grycol derivative	10-30	Trade Secret	Trade Secret
2	Alcohol derivative	20-40	Trade Secret	Trade Secret
3	Pigment (Magenta)	1-5	Trade Secret	Trade Secret
4	Resin	3-8	Trade Secret	Trade Secret
5	Amine	0.5-2	Trade Secret	Trade Secret
6	Water	30-50	7732-18-5	$H_2O$



OSHA Hazardous	<sup>:</sup> This material is considered hazardous.
Components	
(29 CFR 1910. 1200)	

### 4. First Aid Measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable
matation	for breathing. If breathing is difficult, oxygen should be
	administered by qualified personnel. If breathing has stopped, start
	artificial respiration at once. Get immediate medical attention.
Eye Contact	: Flush eyes with plenty of water for at least 15 minutes. Remove
	contact lenses, if present and easy to do. Get immediate medical
	attention.
Skin Contact	: Wash skin with soap and water for at least 15 minutes while
	removing contaminated clothing and shoes. Get medical attention, if
	needed. Thoroughly clean and dry contaminated clothing and shoes
	before reuse.
Ingestion	: If swallowed, get medical attention. Do not give anything by mouth
	to an unconscious person.

# 5. Fire Fighting Measures

See Section 9 for Flammability Properties

NFPA Ratings	: Health: 1 Fire: 1 Reactivity: 0	
	Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate	
	3 = Serious $4 = $ Severe	
Flammable Properties	: This product is not a fire hazard, but may burn. Irritating and/or	
	toxic fumes and gases may be emitted upon the product's	
	decomposition.	
Extinguishing Media	: regular dry chemical, carbon dioxide, water spray, foam	
Fire Fighting	: Wear full protective fire fighting gear including self contained	
Instructions	breathing apparatus (SCBA) for protection against possible	
	exposure.	
	Move container from fire area if it can be done without risk. Do not	



scatter spilled material with high-pressure water streams. Dike for later disposal. Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

### 6. Accidental Release Measures

Occupational spill/release : Wear personal protective clothing and equipment, see Section 8. Collect spilled material in appropriate container for disposal. Keep unnecessary people away, isolate hazard area and deny entry. Avoid creation of vapor or mist.

#### 7. Handling and Storage

Handling	Avoid contact with eyes, skin and clothing. Avoid breathing vapor or
	mist. Wash thoroughly after handling.
Storage	: Store and handle in accordance with all current regulations and
	standards. Store in a tightly closed container. Keep away from
	incompatible materials.

### 8. Exposure Controls / Personal Protection

#### Exposure Limit Values

There are no exposure limit values for any of this product's components.

### Exposure Controls

Occupational Exposure	Controls	
Engineering Controls	: Provide local exhaust ventilation system. Ensure compliance with	
	applicable exposure limits	
Personal Protection		
Respiratory	Any chemical cartridge respirator with organic vapor cartridge(s).	
Protection		
Hand Protection	: Wear appropriate chemical resistant gloves.	
Eye Protection	: Wear splash resistant safety goggles with a faceshield.	
Skin Protection	: Wear appropriate chemical resistant clothing.	



## 9. Physical and Chemical Properties

Appearance	- Physical State	: liquid
	- Color	: Magenta
Odor		: faint
pH		: 10
Boiling Point / Boiling Range		: Not available
Melting Point / Melting Range		: Not available
Flash Point		: None
Density		: Not available
Water Solubility		: soluble
Viscosity		$:13 \text{ mP} \cdot \text{s}$
Vapor Density		: Not available
VOC		:52%

### 10. Stability and Reactivity

Conditions to Avoid	Avoid contact with incompatible materials.
Stability	: Stable at standard temperatures and pressure.
Materials to Avoid	: halogens, oxidizing materials
Hazardous Reactions /	: No reactivity hazard is expected. Hazardous polymerization will not
<b>Decomposition Products</b>	occur.
	Irritating and/or toxic fumes and gases may be emitted upon the
	product's decomposition.

## 11. Toxicological Information

Acute Toxicity	:	Oral LD50(rat)	Dermal LD50(rabbit)
	Water	>90 mL/kg	
	Alcohol derivative	16 g/kg	
	Diethylene grycol derivative	4920 µL/kg	3560µL/kg
	Pigment (Magenta)	>5000 mg/kg	
Irritation	$\vdots$ eye irritation, skin irritation,	respiratory tract	irritation
Medical Conditions	: respiratory disorders		
Aggravated by Exposure			



# 12. Ecological Information : Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch. Ecotoxicity : Components of this product are hazardous to aquatic life 13. Disposal Considerations **Disposal Methods** : Dispose in accordance with all applicable regulations. Do not dump this product into sewers, on the ground or into any body of water. **Component Waste** : The U.S. EPA has not published waste numbers for this product's Numbers components. 14. Transport Information

	Check a thing without a leak in a container.
	Perform prevention of collapse of cargo surely.
US DOT Information	: Not regulated
TDG Information	: Not regulated
UN Number	: Not regulated

# 15. Regulatory Information

# U.S. Federal Regulations

	: None of this products components are listed under SARA Sections		
	302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR		
	370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR		
	302.4), TSCA 12(b), or require an OSHA process safety plan.		
SARA 311/312	: Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No		
	Reactive: No		



HMIS Ratings

Health: 1\* Fire: 1 Reactivity: 0
Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe \* = Chronic hazard

U.S. State Regulations Not regulated.

### 16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

### Revision history

Version	Date	Content
1.0	2012/03/29	First issue