

Revised: 2019/11/25

1. Product and Company Identification

Product Name : Antifreeze
Product Code : SPC-0394

General Use : General cold and heat medium(Food factory), ice storage

refrigerant

Product Description : Antifreeze

MSDS Number : 037-0042470

Manufacture

Company Name : Mimaki Engineering Co., Ltd

Address : 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan

Telephone No. : +81-268-64-2413

Importer/Distributor Established in USA

Company Name : MIMAKI USA. INC.

Address : 150 Satellite Boulevard NE, suite A, Suwanee, Georgia 30024,

U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)

+1 215 207 0061

2. Hazards Identification

[HCS Classification]

Physical Hazards

Flammable Liquids : Not classified

Health Hazards

Acute Toxicity - Oral : Not classified Acute Toxicity - Dermal : Not classified Skin Corrosion / Irritation : Not classified Eye Damage / Irritation : Not classified Sensitization – Respiratory : Not classified Sensitization – Skin : Not classified Germ Cell Mutagenicity : Not classified Specific Target Organ Toxicity : Not classified

(Single Exposure)



Revised: 2019/11/25

Specific Target Organ Toxicity : Not classified

(Repeated Exposure)

Environmental Hazards

Hazardous to the Aquatic : Not classified

Environment - Acute Hazard

Hazardous to the Aquatic : Not classified

Environment - Long Term Hazard

The above list does not include category being non-classifiable or not-applicable.

[HCS Label Elements]

Symbol

None

Signal Word

None

Hazard Statements

None

Precautionary Statements

None

3. Composition / Information On Ingredients

No	Chemical Name	Wt%	CAS No.
1	Propylene glycol	55~60%	57-55-6
2	Additive	3~7%	Trade Secret
3	Water	35~40%	7732-18-5

4. First Aid Measures

Inhalation

: Immediately remove victim to fresh air.

Keep victim warm by covering with a blanket and rest.

If breathing is weak or stopped, loosen clothing and maintain an open airway and then, give artificial respiration.

If unconscious but breathing or if conscious but breathing is difficult, it is effective to give oxygen. It is recommended to conduct under doctor's guidance.

Never administer a dose without doctor's instructions.



Revised: 2019/11/25

Never give anything by mouth to victim.

Immediately get medical attention.

Eye Contact : Remove contact lenses, if present and easy to do. Continue rinsing.

Rinse eyes with clean water for at least 15 minutes and get medical attention form an ophthalmologist immediately. Hold eyelids open and away from eyeballs with fingers to ensure that all surfaces are

flushed thoroughly.

Skin Contact : Remove contaminated clothing, shoes, etc. promptly. Cut it off

necessary. Flush affected area with water or lukewarm water and wash off with soap. If visual change occurs or pain persists, get

medical attention.

If contact with hot liquid, immediately wash with water and

sufficiently cool with ice water.

Immediately get medical attention.

Ingestion If conscious, induce vomiting by giving more than two cups of milk

or water and get medical attention immediately.

Never give water, etc to an unconscious person.

Keep victim warm and get medical attention immediately.

Expected acute and : If swallowed, it can cause diarrhea, vomit.

delayed symptoms, most

important sign and

If in eyes, it can cause inflammation.

If on skin, it can cause inflammation.

symptoms

If inhaled mist, it can cause nausea.

5. Fire Fighting Measures

Extinguishing Media : Use water (water fog), dry powder, and alcohol-resistant foam.

Unsuitable extinguishing : Don't use fire hose.

media

Special risk/hazard : Containers may explode when heated.

Fire Fighting Instructions : Eliminate all sources of ignition form fire area.

For initial fire, use water (water fog), dry powder, etc. for fighting

fire.

For large fire, it is effective to use foam (alcohol-resistant foam), etc

to shut off air supply.

Pouring water can be dangerous by expanding fire.

Cool surrounding facilities, etc. with water spray.



Revised: 2019/11/25

Prohibit unnecessary personnel from entering fire area.

Immediately remove moveable container to a safe area.

: Wear safety glasses, protective clothing, and respiratory protection

for the situation during fire fighting.

Extinguish fire form upwind.

6. Accidental Release Measures

Protection for fire-fighters

Personal precautions, : Prohibit unnecessary personnel from entering spilled area

protective equipment and separated by rope, etc.

emergency measures Wear suitable protective equipment during clean-up to prevent

contact with water drop or inhalation of gas.

Work from upwind and evacuate from downwind.

Precautions for the : Since it is related to soil and water contamination, recover spills as

environment much as possible.

Recovery/neutralization : For large spills, dike with earth and sand, etc. to prevent spreading

and sweep into an empty container and dispose of in a safe place. Be

tender of discharging into sewers, drains, etc. Be sure to wear

protective equipment during clean-up.

For small spills, absorb with dry sand, earth, sawdust, wastes, etc

and collect into an empty container that can be closed.

Method for containment : Stop leakage, if it can be done without risk.

• • •

and clean-up In case of running off, prevent spread of the liquid and scoop or

absorb with a proper absorbent.

If inevitable, use a chemical.

When using a chemical, it should meet the technical standards set

by the Ordinance of the Ministry of Transport.

Preventive measure of : Immediately eliminate all source of ignition nearby.

secondary disaster Request cooperation by giving notice to relevant agencies.

7. Handling And Storage

Handling : Keep good working environment.

Technical measures: Prevent spills, overflow, scattering and generation of vapors.

Prohibit the use of sources of fire, sparks and arcs around the

handling place.



Revised: 2019/11/25

Prohibit the use near sources of ignition of high temperature.

Repair machinery containing residues after completely removing them in a safe place.

Take precautionary measures against static discharge and wear conductive working clothes, shoes, etc.

Since vapors are heavier than air, it is likely to stay in low areas.

So, pay attention to ventilation and sources of fire, etc.

Handle at room temperature and pay attention to mixing with water or impurities.

If it is possible to contact with skin or eyes, wear protective equipment.

If mist is generated, do not breathe mist by wearing respirators, etc.

Use a pump, etc. to take out the product from a container.

Use a thin tube and do not suck it with mouth.

Do not weld, heat, puncture or cut containers. It can cause ignition of residues following explosion.

Local exhaust or general : See 'Section 8. Exposure Controls and Personal Protective

ventilation Equipment'.

Avoid to contact : See 'Section 10. Stability and Reactivity'.

Precaution for safe : Obtain special instruction before use.

handling Do not handle until all safety precautions have been read and

understood.

Pay attention to sources of fire.

Wash hands and eyes thoroughly after handling.

If on clothing, change clothing.

Use only outdoors or in a well-ventilated area.

Do not eat or smoke when using this product.

Do not put pressure to an empty container. It can cause rupture

of a container.

Do not drink.

Keep out of the reach of children.

Storage : Avoid heat, sparks, open flames and static built -up.

Technical measure Be sure to keep container tightly closed. Incompatible materials : See 'Section 10. Stability and Reactivity'.

Storage condition : Keep container in a well-ventilated area.

Protect from direct sunlight.



Revised: 2019/11/25

Keep away from oxidizing agents.

Safe container and : Use container without damage, corrosion, cracks, etc.

packaging material Do not handle a container in a violent manner such as turning over,

impacting or dragging it.

Keep used container at a certain designated place.

8. Exposure Controls / Personal Protection

Controlled exposure level : No regulation.

Exposure Controls

Permissible exposure : The Japanese Occupational Hygiene Society (2009): Not

level(Threshold limits, established.

biological exposure indices, ACGIH (2009): Not established.

etc)

Occupational Exposure Controls

Engineering Controls : If mist and vapor is generated, use enclosure of sources or local

exhaust ventilation.

Provide safety shower, basin and eye wash facilities near the place

where the product is handled and indicate the location clearly.

Personal Protection

Respiratory Protection: : Wear gas mask for toxic gas, if necessary.



Hand Protection

: Wear impermeable rubber gloves.



Eye Protection

: Wear ordinary glass with side shields or safety goggles.



Skin Protection:

: Wear long-sleeved working clothes.

Take off wet clothing and wash before reuse.



Revised: 2019/11/25



General hygiene : Check protective equipment on a regular based on a checklist.

consideration Do not eat or smoke during work.

Wash hands with soap before eating or smoking.

9. Physical And Chemical Properties

Appearance - Physical state : liquid

> - Color : Red clear

Odor : Almost odorless

:8~9 pН

Melting Point / Freezing Point : ≦-40 degrees C

: 107 degrees C/101kPa **Boiling Point**

Flash Point : None. : None. Ignition temperature Explosive limits: Lower : None. Explosive limits: Upper : None.

Vapor pressure : 1.7kPa/20 degrees C

Vapor density(Air=1) : No data.

: 1.05g/cm³(20 degrees C) Specific gravity(Density)

Solubility : Soluble in water, low alcohols, acetone

Partition coefficient(n-octanol/water) : No data. Auto-ignition temperature : No data. : No data. Decomposition temperature

10. Stability And Reactivity

: Stable Stability

Possibilty of hazardous : Explosion/ignition at room temperature hardly occurs, but if

reactions moisture is evaporated at high temperature, it is easy to

ignite/burn.

It can react with strong acids, strong oxidizing agents violently.

Conditions to avoid : No data. (No hazardous reactions under normal handling

condition.)



Safety Data Sheets

Product Name: Antifreeze SDS No. 037-0042470 First issue: 2011/07/05 Revised: 2019/11/25

Incompatible materials : Strong acids, strong oxidizing agents.

Hazardous decomposition : No data.

products

11. Toxicological Information

Acute Toxicity	te Toxicity : (Annex) Acute toxicity(Oral, dermal, inhalation)						
	Content	Oral	Dermal	Inhalation	Inhalation	Inhalation	
	(%)			(Gas)	(Vapor)	(Dust, mist)	
1.Propylene glycol	55~60%	Not	Not	Not	Classificati	Classificati	
		classified	classified	applicable	on not	on not	
					possible	possible	
2. Additive	3~7%	Classifica	Classifica	Not	Classificati	Classificati	
		tion not	tion not	applicable	on not	on not	
		possible	possible		possible	possible	
3.Water	35~40%	Not	Not	Not	Not	Not	
		classified	classified	applicable	classified	classified	
Total	100%						

Oral : It contains acute toxicant (oral) on Annex.

Acute toxicity (oral) estimation, ATEmix=33,333mg/kg is

calculated by GHS criteria.

The product as a mixture is classified as 'Acute toxicity (Oral): Not

classified'.

Dermal : It contains acute toxicant (dermal) on Annex.

Acute toxicity (dermal) estimation, ATEmix=37,500mg/kg is

calculated by GHS criteria.

The product as a mixture is classified as 'Acute toxicity (Dermal):

Not classified'.

Inhalation : It contains acute toxicant (inhalation) on Annex.

The product as a mixture is not possible to classify for acute

toxicity(inhalation).

Serious eye damage/eye

: It contains eye irritants classified below.

irritation

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Serious eye damage/eye



Revised: 2019/11/25

irritation: Not classified'.

Serious eye damage/eye irritation of 3~7% of this mixture is

unknown.

Skin corrosion/irritation : It contains skin irritants classified below.

-Not classified: Water, Propylene glycol.

The product as a mixture is classified as 'Skin corrosion/irritation:

Not classified'.

Skin corrosion/irritation of 3~7% of this mixture is unknown.

Respiratory or skin

: It contains respiratory sensitizers classified below.

sensitization

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Respiratory sensitization:

Not Classified'.

Respiratory sensitization of 3~7% of this mixture is unknown.

It contains skin sensitizers classified below.

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Skin sensitization: Not

classified'.

Skin sensitization of 3~7% of this mixture is unknown.

Germ cell mutagenicity

:It contains germ cell mutagens classified below.

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Germ cell mutagenicity:

Not classified'.

Germ cell mutagenicity of 3~7% of this mixture is unknown.

Carcinogenicity

: Classification is not possible due to lack of data.

Reproductive toxicity

: Classification is not possible due to lack of data.

Specific target organ

: It contains specific target organ toxicants(single

toxicity (single exposure)

exposure)classified below.

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Specific target organ

toxicity (single exposure): Not classified'.

Specific target organ

: It contains specific target organ toxicants(repeated

toxicity (repeated

exposure)classified below.

exposure)

-Not classified: Water

:The product as a mixture is classified as 'Specific target organ

toxicity(repeated exposure): Not classified'.

Aspiration hazard

: Classification is not possible due to lack of data.



Revised: 2019/11/25

12. Ecological Information

Ecotoxicity : It contains hazardous substances(acute)to aquatic environment

classified below.

-Not classified: Water, propylene glycol

The estimation of hazards to aquatic environment (acute)

LC50=166.7mg/L is calculated by GHS criteria.

The product as a mixture is classified as 'Hazards to aquatic

environment (Acute): Not classified'.

Hazards to aquatic environment (Acute) of 3~7% of this mixture is

unknown.

It contains hazardous substances (chronic) to aquatic environment

classified below.

-Not classified: Water, propylene glycol

The product as a mixture is classified as 'Hazards to aquatic

environment (Chronic): Not classified'.

Hazards to aquatic environment (Chronic) of 3~7% of this mixture

is unknown.

Persistence/degradability : No data.

Bio-accumulation : No data.

Mobility in soil : No data.

Other adverse effects : No data.

Environment criteria : No data.

13. Disposal Considerations

Residual wastes : Dispose the waste according to national and local regulations.

Do not dump.

Contaminated container

and packages

: Contaminated or empty container packaging are to be disposed

according to national and local regulations.

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information



Safety Data Sheets

Product Name: Antifreeze SDS No. 037-O042470 First issue: 2011/07/05

Revised: 2019/11/25

US DOT Information : Not regulated as a hazardous material for transport.

TDG Information : Not regulated as dangerous goods for transport. IATA Information : Not regulated as dangerous goods for transport. **ICAO** Information : Not regulated as dangerous goods for transport.

: Not regulated as dangerous goods for transport. **IMDG** Information

Special precautions : Load the containers in a manner that they are certain not to result

in direct sunlight exposure, damage, corrosion, leak, while being

transport.

Load the containers in manner that they are not to fall apart while

being transport.

Do not place heavy load on top of the container. Check a thing without a leak in a container. Perform prevention of collapse of cargo surely.

15. Regulatory Information

US federal regulations : All components are active on the TSCA Inventory List.

16. Other Information

References 1) The Japanese Occupational Hygiene Society recommendation on

permissible exposure level, etc (OELs)

2) Thresholds limit values for chemical substances and physical

agents and biological exposure indices. ACGIH

3) Material Safety Data Sheet (Propylene glycol), Japan

Petrochemical Industry Association (1998)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.