

# Safety Data Sheets

### 1. Identification

Product Name	: IJ Primer PR-200	
Order No.	: PR200-Z-22 / PR200-Z-60 / PR200-Z-BA / PR200-Z-B2 / PR200-Z-CA/	
	PR200-Z-C6	
Ink Ver	:2	
General Use	: Primer for ink jet printer	
Product Description	: The undercoating liquid	
SDS Number	: 037-O060306	
Manufacture		
Company Name	: Mimaki Engineering Co., Ltd.	
Address	2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN	
Telephone No.	:+81-268-64-2413	
Importer / Distributor Esta	blished in USA	
Company Name	: MIMAKI USA, INC.	
Address	: 150 Satellite Boulevard NE , suite A, Suwanee, Georgia 30024,	
	U.S.A.	
Telephone No.	: +1-678-730-0170	
Emergency Telephone No.	: +1 866 928 0789 (within United States only, Toll free)	
	$+1\ 215\ 207\ 0061$	

## 2. Hazards Identification

[HCS Classification]			
Physical Hazards			
Flammable Liquids	: Not classified		
Substances and Mixtures, which in	: Not classified		
Contact with Water, Emit Flammable			
Gases			
Health Hazards			
Skin Corrosion / Irritation	Category 2		
Eye Damage / Irritation	: Category 2		
Sensitization - Skin	: Category 1		
Environmental Hazards			
Hazardous to the Aquatic	: Category 2		
Environment - Acute Hazard			



Product Name: IJ Primer PR-200 SDS No. 037-0060306 First issue: 2015/07/23 Revised: 2021/11/17

## Safety Data Sheets

Hazardous to the Aquatic

: Category 2

Environment - Long Term Hazard

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements] Symbol



Signal Word Warning Hazard Statements H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H411 Toxic to aquatic life with long lasting effects **Precautionary Statements** [Prevention] P261 Avoid breathing gas/mist/vapours. P264 Wash hands and eyes thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. Response P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. [Disposal] P501 Dispose of contents and container in accordance with local, regional, national and international regulation (to be specified).

Statement(s) of Unknown Aquatic Toxicity

45% of the mixture consists of ingredient(s) of unknown acute aquatic toxicity.

40% of the mixture consists of ingredient(s) of unknown chronic aquatic toxicity.

HMIS Rating (scale 0 - 4)

NFPA Rating (scale 0 - 4)

Health = 1Health = 1(1)Health Flammability = 0Flammability=0 **0** Flammability  $(\mathbf{0})$ Reactivity age 2 of 13 Protective Equipment

# **MINCIKI** Safety Data Sheets

Reactivity = 0 Protective Equipment =

Instability = 0 Special =

#### 3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1 Aliphatic monomer		40-50	Trade Secret
2	Acrylic oligomer	25-35	Trade Secret
3	Aromatic monomer	15-25	Trade Secret
4	Photo-initiator	<10	Trade Secret
5	Additives	<10	Trade Secret

\*Acrylic oligomer contains acrylic acid and toluene. And aromatic monomer contains phenyl glycidyl ether

#### 4. First Aid Measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable	
	for breathing. Get medical advice/ attention if you feel unwell.	
	Get medical advice/ attention if experiencing respiratory symptom.	
	Cover body with blanket to warm and keep at rest. Perform CPR if	
	not breathing.	
Eye Contact	Rinse cautiously with water for several minutes. Remove contact	
	lenses, if present and easy to do. Continue rinsing. Rinse with clean	
	water for at least 15 minutes and then seek medical attention if	
	necessary. When rinsing, open your eyelids with fingers to insure	
	saturation of water. Seek medical attention if the problem persists.	
Skin Contact	: Remove/ Take off all contaminated clothing immediately. Wash with	
	plenty of soap and water. Get immediate medical advice/ attention, if	
	skin irritation or rash occurs.	
Ingestion	Rinse mouth. Do not give an unconscious person anything to drink.	
	Get immediate medical advice/ attention. If vomiting occurs, lean	
	patient forward or place on left side (head-down position, if possible)	
	to maintain open airway and prevent aspiration. Do not induce	
	vomiting.	
Protection To First-Aiders	: Wear appropriate protective equipment if necessary.	



Product Name: IJ Primer PR-200 SDS No. 037-0060306 First issue: 2015/07/23 Revised: 2021/11/17



5. Fire Fighting Measure	s		
Flammable Properties	: Flash point : Approx 106 °C		
	Ignition point : Not available		
	Flammable point : Not available		
Extinguishing Media	: <u>Suitable extinguishing media</u>		
	Fire-extinguishing powder, fire-fighting foam, carbon dioxide, sand,		
	water spray		
	<u>Unsuitable extinguishing media</u>		
	High pressure water jet.		
Specific hazards arising	: When exposed to high temperatures, this product may generate		
from product	dangerous decompositions such as nitrogen oxides carbon monoxide,		
	carbon dioxide, and sulfur dioxide.		
Specific extinguish	: Cut off the combustion source to the origin of fire and extinguish by		
measures	using the appropriate fire extinguishing media. Firefighting		
	measures should be done from windward as much as possible.		
	Take appropriate measures to disallow substances that may affect		
	the environment from being dispersed by the drainage. Remove all		
	containers possible to a safe place promptly. If not possible to		
	remove, cool down the area. Work from windward and avoid		
	inhaling any harmful gases. Use respiratory equipment if necessary.		
Special protective	: Cut off the combustion source to the origin of fire and extinguish by		
equipment and	using extinguishing media. Combustion / Flue gases generate		
precautions	carbon monoxide and etc. To avoid the fire from spreading, cool		
	surrounding area with water spray. Extinguish from windward and		
	avoid inhaling any harmful gases. Use respiratory equipment if		
	necessary. Extinguish from the windward where the gases do not		
	accumulate and prevent the leakage from spreading. Wear		
	appropriate protective wear (heat-proof) including air respirators.		
	Wear respiratory equipment for harmful gases are produced from		
	combustion or high temperature.		



#### 6. Accidental Release Measures

Personal Precautions	: Avoid breathing gas / mist/vapours. Wear protective equipment (boots, gloves, and glasses) to prevent contact with skin. Remove ignition sources in the area and work from windward. Clean up immediately when it spills on the floor or any surface. (The floor surface becomes slippery). Prohibit entry other than related personnel. Ventilate released area. Do not touch and/or walk in the spills. The worker wears an appropriate protective equipment, and avoids eyes, the skin contacts, and inhalations. (refer to Section 8)
	Provide adequate ventilation if indoors. Cordon off the area and prevent entry of non-related personnel. Work from windward and
	remove personnel downwind of the area. Wear appropriate
	protective equipment to prevent contact with skin and inhaling
	fumes. Remove ignition sources in the area promptly. Prepare fire
	extinguishing equipment in case of ignition.
Environmental	Avoid releasing to the environment. Collect spillage. Do not empty
precautions	into drain. If it is mixed with wastewater, drain it after the activated
	sludge process. Be careful not to influence living organisms and
	water quality in the environment by products released into rivers
	and any type of body of water. Contact local authorities if it is
	flowing into rivers or any type of body of water as necessary. Be
	careful not to influence the environment by products released into
	rivers or any type of body of water. If the pollution of water pipes or
	waterways occur, contact relevant organizations. Clean the area and
	avoid entry into plumbing system. Be careful not to drain or release
	untreated waste water into the environment.
Methods and materials	: Contain the flow path with blankets or sand bags and collect into an
for recovery and	appropriate container for large spills. Gather and collect into a
neutralization	container for small spills. Prevent the inflow into drains, sewer,
	basement, or enclosed areas. Clean spills frequently as there is
	danger of slipping on remnants. Remove all ignition sources.
	Smoking, open flame or ignition sources are not allowed in the area.
	Contain with consideration to safety. Collect into open container by
	absorbing with cloths, rags, sand or etc. and then rinse with plenty

# **Mimaki** Safety Data Sheets

of water. Collect what has scattered into a container that can be sealed. Clean the spilled area with a cloth or a rag. Wear appropriate protective equipment throughout the process.

#### 7. Handling and Storage

Relevant regulation shall be subject to where this product will be handled and stored.

Handling : Work in accordance with the Occupational Safety and Health Act and related laws and regulations. Keep the concentration below the allowed limit. Avoid inhalation and contact. Wear protection if risk of exposure occurs. Use only in a well-ventilated area. Avoid smoking, open flames, heat and sources of ignition. Always cleanse with soap and water after handling. Determine proper procedures for compliance. Seal container after use. Avoid leakage, overflow, dispersal and generating steam without any good reason. Avoid improper handling like tipping over, dropping, strong impact to or dragging the container. Wash hands thoroughly and rinse mouth after handling. Do not eat, drink or smoke when using this product. Do not carry contaminated gloves and protective equipment into rest / break areas. Prohibit entry to work areas other than related personnel. Collect used containers in a defined / fixed area. Use containers that are not damaged, corroded or cracked. Use local exhaust ventilation systems indoors work areas. Wear proper protective equipment to avoid inhalation and contact with eyes and skin. Storage : Store in a well-ventilated area. Protect from sunlight (Ultra Violet-light). Keep container tightly closed. Keep cool. Store in a dark

light-safe area. Do not freeze.



#### 8. Exposure Controls / Personal Protection

Exposure Limit values · Not specified			
No	Chemical Name		TWA
1	Acrylic compound	ACGIH	2ppm
2		OSHA	10ppm
2 Aromatic compound	Aromatic compound	ACGIH	0.1ppm
3	Additives	ACGIH	2mg/m <sup>3</sup> (IFV)

Exposure Limit Values : Not specified

TWA : Time Weighted Average, IFV : As inhalable fraction and vapor.

#### **Exposure Controls**

Safety Glasses

**Occupational Exposure Controls** 

Engineering Controls	: In the case of indoor use, contain at the source or install a local exhaust system. Provide safety shower and eye / hand wash stations		
	and identify the area clearly. Contain at the source and install a local		
	exhaust system if dust is generated.		
Personal Protection	: Wear following protective equipment as necessary and accordingly.		
	Inspect equipment on a regular basis by using a protective equipment		
	maintenance chart.		
Respiratory	: Supplied air respirator, air/ oxygen breathing apparatus, organic		
Protection	vapor gas mask		
Vapor Respirator			
Hand Protection	: We aring gloves that organic solvents or chemicals do not penetrate is		
Gloves	preferred.		
Eye Protection	: Wear coverall, chemical goggles and face shield when handling.		





: Wearing protective clothing (long sleeve uniform) that organic solvent or the chemical do not infiltrate easily preferred.

Environmental Exposure Controls

: Not available

#### 9. Physical and Chemical Properties

Appearance - I	Physical State	: liquid
- (	Color	: Yellow
Odor		: Faint
pH		: Not Applicable
Boiling Point / Bo	oiling Range	∶Approx 181℃
Melting Point / Melting Range		: Not available
Flash Point		∶Approx 106℃
Relative Density		: Approx 1.1mg/cm <sup>3</sup>
Solubility		: Not available
Water Solubility		: Not available
Partition Coefficient (n-octanol / Water)		: Not available
Viscosity		: Not available

#### 10. Stability and Reactivity

Reactivity	: Decomposes upon heating and produces carbon dioxide and carbon monoxide.
~	
Conditions to Avoid	Sunlight, heat, open flame, high temperature, sparks, static
	electricity, other sources of ignition.
Stability	: Stable under normal conditions.
Materials to Avoid	: Incompatible with acid, alkali, amines and is prohibited to mix with.
Hazardous Reactions /	: Carbon monoxide (CO), carbon dioxide (CO2) gas might be generated
Decomposition Products	by combustion. Vapor from organic solvents.



#### 11. Toxicological Information

Acute Toxicity	: ORAL		
	Product	LD50(rat) : >2000 mg/kg	
	DERMAL	·	
	Product	LD50(rat) : >2000 mg/kg	
Eye Irritation	Causes severe eye irrita	tion. Category 2 as a product.	
	Aliphatic compound	Category 2	
	Aromatic compound	Category 2	
Skin Irritation	Causes moderate skin ir	ritation. Category 2 as a product.	
	Aliphatic compound	Category 2	
	Aromatic compound	Category 2	
Skin Sensitization	: May cause an allergic sk	in reaction. Category 1 as a product.	
	Aromatic compound	Category 1	
Mutagenicity	: No information available	2.	
Carcinogenicity	: No information available	: No information available.	
Reproductive and Developmental Toxicity			
	: No information available.		
Specific Target Organ Toxicity (Single Exposure)			
: No information available.			
Specific Target Organ Toxicity (Repeated Exposure)			
	: No information available	2.	
Aspiration hazard	: No information available	е.	

### 12. Ecological Information

	Handling is noted because it might influence the environment when		
	leaking and abandoning it.		
	Especially, note that the product doesn't flow directly to ground, the		
	river, and the drain ditch.		
Ecotoxicity	: Toxic to aquatic life.	: Toxic to aquatic life.	
	Aliphatic compound Category	y 2	
Persistence and	: No information available.		
degradability			



: No information available.
: No information available.
: No information available.

#### 13. Disposal Considerations

Comply with all USA, national and local regulations. A contaminated container and packing are disposed of after removing extraneous matter thoroughly. Follow all regulations in your country or regions.

Do not dump this product into sewers, on the ground or into any body of water.

#### 14. Transport Information

Use a container provided for in the UN Recommendations on the TDG Model Regulations. Avoid direct sunlight during transportation. Confirm the container has no damage, corrosion, leakage before transportation. Take measures to prevent the load from tipping, falling and damages. Follow all regulations on the transport in your countries regions. Verify the container as no leaks when transporting and take preventative measure when loading so that the cargo does not tip, fall or get damaged during transit.

UN Number	: 3082					
Proper Shipping Name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID					
	N.O.S(Aliphatic monomer)					
Transport hazard	: 9 (Miscellaneous dangerous substances & articles)					
class(es)						
Packing Group(PG)	: III					
Marine Pollutant	: Yes (Product)					
Remarks	: Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is					
	excepted from Dangerous Goods regulations.					
	Refer to ICAO/IATAA197, IMDG 2.10.2.7, ADR SP 375.					



## Safety Data Sheets

15. Regulatory Information	ı					
<b>U.S Federal Regulation</b>	: None of this products components are listed under SARA Sections					
	302/304, SARA Section 313, CERCLA.					
	SARA Section 311/312 reporting categories: Skin Irritation; Skin					
	Sensitization; Eye Irritation					
TSCA INVENTORY	:					
	Chemical	name	TSCA INVE	NTORY		
	Aliphatic	monomer	Listed			
	Acrylic oli	gomer	No Listed			
	Aromatic	monomer	Listed			
	Photo-init	iator	Listed			
	Additives		Listed			
SARA Section 311/312	: Acute Health: Yes					
(40 CFR 370 Subparts B	Chronic Health: Yes					
and C) 2016 reporting	Fire: No					
categories	Pressure: No					
	Reactivity: No					
California Proposition 65	: <b>WA</b>	RNING				
	This product can expose you to chemicals including Phenyl					
	glycidyl ether and Toluene, which are known to the State of					
	California to cause cancer/ birth defects or other reproductive					
	harm. For more information go to www.P65Warnings.ca.gov.					
	California Proposition 65:					
	Chemica	l name	CAS-No.	wt%	MADL	
	Phenyl g	lycidyl ether	122 - 60 - 1	< 0.1	5.0 µg/day	
	Toluene		108-88-3	< 0.1	7000 µg/day	
Others	Please refer	to any other f	ederal, state a	and local reg	gulations.	

#### 16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.



Product Name: IJ Primer PR-200 SDS No. 037-0060306 First issue: 2015/07/23 Revised: 2021/11/17

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.