

1. Identification

Product Name	SS21 ink Light Black
Order No.	: SPC-0501LK-2 / SPC-0588LK-2 / SS21-LK-60-2
Ink Ver.	:2
General Use	: Ink for ink jet printer
Product Description	: Solvent pigment ink
SDS Number	: 037-S080269
Manufacture	
Company Name	: Mimaki Engineering Co., Ltd.
Address	: 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN
Telephone No.	: +81-268-64-2413
Importer / Distributor Esta	ablished in USA
Company Name	: MIMAKI USA, INC.
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.
Telephone No.	: +1-678-730-0170
Emergency Telephone No.	: +1 866 928 0789 (within United States only, Toll free)
	$+1\ 215\ 207\ 0061$

2. Hazards Identification

[GHS Classification] Physical Hazards Flammable Liquids	: Category 4
Health Hazards	
Eye Damage / Irritation	: Category 1
Carcinogenicity	: Category 2
Toxic to Reproduction	: Category 1B
Specific Target Organ Toxicity	: Category 2
(Single Exposure)	
Specific Target Organ Toxicity	: Category 2
(Repeated Exposure)	

The above list does not include category being non-classifiable or not-applicable.



Product Name: SS21 ink Light Black SDS No. 037-S085991 First issue: 2022/04/01 Revised: 2022/05/18

[GHS Label Elements]



Signal Word Danger

Hazard Statements

H227 Combustible liquid.

H318 Cause serious eye damage.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H371 May cause damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

 $\mathrm{P210}$ Keep away from open flames and other ignition sources. No smoking.

P260 Do not breathe gas/mist/vapours.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection. [Response]

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician. (P305+)P310 (IF IN EYES) Immediately call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use foam, carbon dioxide, dry chemical for extinguish. [Storage]

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

NFPA Rating (scale 0 - 4)

Health = 3 Flammability = 2 Instability = 0 Special = None



CANADIAN WHMIS SYMBOLS





3. Composition / Information on Ingredients

Mixtures

No	Chemical Name	Wt%	CAS No.
1	Glycol ether solvents	75-85	Trade Secret
2	Lactone solvent series	10-20	Trade Secret
3	Vinyl resin	1-5	Trade Secret
4	Pigment	0.1-1	Trade Secret
5	Pigment(green)	0.1-1	Trade Secret
6	Corrosion inhibitor	0.1-1	Trade Secret

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Description of first aid measures

Eye Contact	: If this product comes in contact with the eyes:
	Immediately hold eyelids apart and flush the eye continuously with
	running water. Ensure complete irrigation of the eye by keeping
	eyelids apart and away from eye and moving the eyelids by
	occasionally lifting the upper and lower lids. Continue flushing until
	advised to stop by the Poisons Information Centre or a doctor, or for
	at least 15 minutes. Transport to hospital or doctor without delay.
	Removal of contact lenses after an eye injury should only be
	undertaken by skilled personnel.
Skin Contact	: If skin or hair contact occurs:
	Flush skin and hair with running water (and soap if available). Seek
	medical attention in event of irritation.
Inhalation	: If fumes, aerosols or combustion products are inhaled remove from
	contaminated area. Other measures are usually unnecessary.
Ingestion	: Immediately give a glass of water. First aid is not generally
	required. If in doubt, contact a Poisons Information Centre or a
	doctor.
Most important symptom	s and effects, both acute and delayed

See Section 11.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



5. Fire Fighting Measures			
Flammable Properties	: Flash point 64.7 degree C		
	Auto Ignition Temperature: 169 degree C		
	Explosive Limit : 2% to 33.0%		
Extinguishing Media	: Foam, Dry chemical powder, BCF (where regulations permit),		
	Carbon dioxide, Water spray or fog - Large fires only.		
Unsuitable Extinguishing	: Do not scatter spilled material with high-pressure water streams.		
Media			
Special hazards arising from	n the substrate or mixture		
Fire	: None known.		
Incompatibility			
Special protective equipment	t and precautions for fire-fighters		
Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard.		
	Wear full body protective clothing with breathing apparatus.		
	Prevent, by any means available, spillage from entering drains or		
	water course. Use water delivered as a fine spray to control fire and		
	cool adjacent area. Avoid spraying water onto liquid pools.		
	DO NOT approach containers suspected to be hot. Cool fire exposed		
	containers with water spray from a protected location.		
	If safe to do so, remove containers from path of fire.		
Fire/Explosion	: Combustible.		
Hazard	Slight fire hazard when exposed to heat or flame. Heating may		
	cause expansion or decomposition leading to violent rupture of		
	containers. On combustion, may emit irritating/ toxic fumes. May		
	emit acrid smoke. Mists containing combustible materials may be		
	explosive.		
	May emit poisonous fumes.		
	May emit corrosive fumes.		

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures See section 8. Environmental precautions See section 12. **MIMCIKI** Safety Data Sheets

Methods and material for containment and cleaning up

Minor Spills	: Remove all ignition sources. Clean up all spills immediately.
	Avoid breathing vapours and contact with skin and eyes. Control
	personal contact with the substance, by using protective equipment.
	Contain and absorb spill with sand, earth, inert material or
	vermiculite. Wipe up. Place in a suitable, labelled container for waste
	disposal.
Major Spills	: Moderate hazard.
	Clear area of personnel and move upwind. Alert Fire Brigade and
	tell them location and nature of hazard. Wear breathing apparatus
	plus protective gloves. Prevent, by any means available, spillage
	from entering drains or water course. No smoking, naked lights or
	ignition sources. Increase ventilation. Stop leak if safe to do so.
	Contain spill with sand, earth or vermiculite. Collect recoverable
	product into labelled containers for recycling. Absorb remaining
	product with sand, earth or vermiculite. Collect solid residues and
	seal in labelled drums for disposal. Wash area and prevent runoff
	into drains. If contamination of drains or waterways occurs, advise
	emergency services.

7. Handling and Storage

Precautions for Safe Handling	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid smoking, naked lights or ignition sources. Avoid contact with
	incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid
	physical damage to containers. Always wash hands with soap and
	water after handling. Work clothes should be laundered separately.
Conditions for Safe	: Store in original containers. Keep containers securely sealed.
Storage	No smoking, naked lights or ignition sources. Store in a cool, dry,
	well-ventilated area. Store away from incompatible materials and
	foodstuff containers. Protect containers against physical damage and
	check regularly for leaks. Observe manufacturer's storage and
	handling recommendations contained within this SDS.
Storage	: None known.



incompatibility

8. Exposure Controls / Personal Protection

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
OSHA-	Digmont	Carbon black	3.5	Not	Not	Not
PELs	Pigment	Carbon black	mg/m3	Available	Available	Available
ACGIH	Pigment	Carbon black	3	Not	Not	TLV® Basis:
-TLV	rigment	Carbon black	mg/m3	Available	Available	Bronchitis
		Acetylene black,				
NIOSH	Pigment	Channel black, Furnace black,	3.5	Not	Not	Ca See Appendix
-RELs		Lamp black,	mg/m3	Available	Available	A See Appendix C
		Thermal black				

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Pigment	Carbon black	9 mg/m3	99 mg/m3	590 mg/m3
Pigment(green)	Trade secret	12 mg/m3	130 mg/m3	790 mg/m3
Vinyl resin	Trade secret	120 mg/m3	1,300 mg/m3	7,900 mg/m3
Lactone solvent series	Trade secret	3.6 mg/m3	39 mg/m3	310 mg/m3

Ingredient	Original IDLH	Revised IDLH
Pigment	N.E. mg/m3 / N.E. ppm	1,750 mg/m3
Pigment(green)	Not Available	Not Available
Vinyl resin	Not Available	Not Available
Glycol ether solvents	Not Available	Not Available
Lactone solvent series	Not Available	Not Available
Corrosion inhibitor	Not Available	Not Available

Exposure Controls

Occupational Exposure Controls

Appropriate

Engineering Controls

: General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate

MIMCIKI Safety Data Sheets

ventilation in warehouse or closed storage areas.

Personal Protection Respiratory

Protection



Hand Protection



Eye Protection



Skin Protection



: Consult with a health and safety professional for specific respirators appropriate for your use.

: Wear chemical protective gloves, e.g. PVC.

: Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

: Wear safety footwear or safety gumboots, e.g. Rubber. Overalls. P.V.C. apron.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance: Black liquid

Physical state	Liquid	Relative density (Water = 1)	0.974
Odour	Slight	Partition coefficient	Not Available
		n-octanol / water	
Odour threshold	Not Available	Auto-ignition temperature	169
		(°C)	
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point /freezing point	Not Available	Viscosity (cSt)	Not Available
(°C)			
Initial boiling point and	176-204	Molecular weight (g/mol)	Not Available
boiling range (°C)			
Flash point (°C)	64.7 (closed cup)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible	Oxidising properties	Not Available



Upper Explosive Limit (%)	33	Surface Tension (dyn/cm or	Not Available
		mN/m)	
Lower Explosive Limit (%)	2	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	2.67	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

10. Stability and Reactivity

Reactivity	Stable under normal conditions of use.	
Chemical Stability	: Unstable in the presence of incompatible materials.	
	Product is considered stable.	
Possibility of Hazardous	: Hazardous polymerisation will not occur.	
Reactions		
Conditions to Avoid	: See section 7.	
Incompatible Materials	: See section 7.	
Hazardous	: See section 5.	
decomposition products		

11. Toxicological Information

Information on toxicological effects

Inhaled	: The material is not thought to produce adverse health effects or		
	irritation of the respiratory tract (as classified by EC Directives using		
	animal models). Nevertheless, good hygiene practice requires that		
	exposure be kept to a minimum and that suitable control measures be		
	used in an occupational setting.		
Ingestion	\therefore The material has NOT been classified by EC Directives or other		
	classification systems as 'harmful by ingestion'. This is because of the		
	lack of corroborating animal or human evidence.		
Skin Contact	\vdots The liquid may be miscible with fats or oils and may degrease the skin,		
	producing a skin reaction described as non-allergic contact dermatitis.		
	The material is unlikely to produce an irritant dermatitis as described		
	in EC Directives.		
	Open cuts, abraded or irritated skin should not be exposed to this		
	material		
	Entry into the blood-stream, through, for example, cuts, abrasions or		

MIMCIKI Safety Data Sheets

	lesions, may produce systemic injury with harmful effects. Examine
	the skin prior to the use of the material and ensure that any external
	damage is suitably protected.
Eye	: If applied to the eyes, this material causes severe eye damage.
Chronic	: Ample evidence exists from experimentation that reduced human
	fertility is directly caused by exposure to the material.
	Ample evidence exists, from results in experimentation, that
	developmental disorders are directly caused by human exposure to the
	material.

Ingredient	TOXICITY	IRRITATION
As a product	Not Available	Not Available
Pigment	Not Available	Not Available
Pigment(green)	Not Available	Not Available
Vinyl resin	Not Available	Not Available
Glycol ether solvents	Not Available	Not Available
Lactone solvent series	Not Available	Not Available
Corrosion inhibitor	Not Available	Not Available

Acute Toxicity	Data Not Available to make classification.
Skin	Data Not Available to make classification.
Irritation/Corrosion	
Serious Eye	Data available to make classification.
Damage/Irritation	
Respiratory or Skin	Data Not Available to make classification.
sensitisation	
Mutagenicity	Data Not Available to make classification.
Carcinogenicity	Data available to make classification.
Reproductivity	Data available to make classification.
STOT - Single Exposure	Data available to make classification.
STOT - Repeated	Data available to make classification.
Exposure	
Aspiration Hazard	Data Not Available to make classification.



Product Name: SS21 ink Light Black SDS No. 037-S085991 First issue: 2022/04/01 Revised: 2022/05/18

Safety Data Sheets

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Pigment	LC50	96	Fish	=1000mg/L	1
	EC50	24	Crustacea	>5600mg/L	1
	NOEC	96	Fish	=1000mg/L	1
	LC50	96	Fish	713.772mg/L	3
Glycol ether solvents	EC50	96	Algae or other aquatic plants	4246.290mg/L	3
	EC50	384	Crustacea	163.553mg/L	3
	LC50	96	Fish	220mg/L	1
	EC50	48	Crustacea	>500mg/L	1
solvent series EC2	EC50	96	Algae or other aquatic plants	16.400mg/L	3
	EC20	72	Algae or other aquatic plants	=14mg/L	1
	NOEC	24	Fish	=5mg/L	1
Corrosion inhibitor	LC50	96	Fish	1514.080mg/L	3
	EC50	48	Crustacea	374mg/L	2
	EC50	96	Algae or other aquatic plants	61.454mg/L	3
	EC50	504	Crustacea	59.8mg/L	2
	NOEC	504	Crustacea	3.99mg/L	2

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances – Ecotoxicological

Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated)

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
Glycol ether solvents	LOW	LOW	
Lactone solvent series	LOW	LOW	
Corrosion inhibitor	LOW	LOW	
Bioaccumulative potential			
т 1. ,			

Ingredient Bioaccumulation



Glycol ether solvents	LOW (LogKOW = 0.0093)
Lactone solvent series	LOW (BCF = 1.8)
Corrosion inhibitor	LOW (LogKOW = -0.6047)
Mobility in soil	
Ingredient	Mobility
Glycol ether solvents	LOW (KOC = 10)
Lactone solvent series	LOW (KOC = 7.134)
Corrosion inhibitor	HIGH (KOC = 1)

13. Disposal Considerations

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

Disposal Methods	[:] Dispose in accordance with all applicable regulations.	
Disposal of	: Empty containers may contain product residue. Dispose in	
Contaminated	accordance with all applicable regulations.	
Packaging		

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely. Labels Required : Marine Pollutant; NO Land transport (DOT) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS. *1 Air transport : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS. (ICAO-IATA / DGR)

Sea transport: NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS.(IMDG-Code / GGVSee): Not ApplicableTransport in bulk: Not Applicableaccording to Annex II of: MARPOL and the IBC

code

*1 Class combustible liquid (NA1993), Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities



15. Regulatory Information

Safety, health and environmental regulations / legislation specific for the substance or mixture PIGMENT IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US Alaska Limits for Air Contaminants
- US California Permissible Exposure Limits for Chemical Contaminants
- US California Proposition 65 Carcinogens
- US Hawaii Air Contaminant Limits
- US Idaho Limits for Air Contaminants
- US Massachusetts Right To Know Listed Chemicals
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US New Jersey Right to Know Special Health Hazard Substance List (SHHSL): Carcinogens
- US Oregon Permissible Exposure Limits (Z-1)
- US Pennsylvania Hazardous Substance List
- US Rhode Island Hazardous Substance List
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US ACGIH Threshold Limit Values (TLV)
- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US Priority List for the Development of Proposition 65 Safe Harbor Levels No Significant Risk
- Levels (NSRLs) for Carcinogens and
- Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory
- PIGMENT (GREEN) IS FOUND ON THE FOLLOWING REGULATORY LISTS
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory
- VINYL RESIN IS FOUND ON THE FOLLOWING REGULATORY LISTS
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory
- GLYCOL ETHER SOLVENTS ARE FOUND ON THE FOLLOWING REGULATORY LISTS
- US California OEHHA/ARB Acute Reference Exposure Levels and Target Organs (RELs)
- US California OEHHA/ARB Chronic Reference Exposure Levels and Target Organs (CRELs)



US - Pennsylvania - Hazardous Substance List

US Clean Air Act - Hazardous Air Pollutants

US EPCRA Section 313 Chemical List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

LACTONE SOLVENT SERIES ARE FOUND ON THE FOLLOWING REGULATORY LISTS

US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

CORROSION INHIBITOR IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	Yes
Fire hazard	Yes
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported.

State Regulations

US. CALIFORNIA PROPOSITION 65

: WARNING:
This product can expose you to chemicals including Arsenic compounds, Cadmium and
cadmium compounds, Carbon black, Chromium (hexavalent compounds), Lead and
lead compounds, Mercury and mercury compounds, Nickel compounds, Vinyl Chloride,
Ethylene Glycol Monoethyl Ether, Acetaldehyde and Methanol which are known to the
State of California to cause cancer/ birth defects or other reproductive harm. For more
information go to www.P65Warnings.ca.gov.

Inventory

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y



Canada - NDSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Ν
USA - TSCA	Y

Legend: Y = All ingredients are on the inventory.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets).

16. Other Information

Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.