

Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

1. IDENTIFICATION

Product Identifier SS22 Yellow

Product code SS22-Y-1L / SS22-Y-44 Recommended use of the chemical and Ink for ink jet printer

restrictions on use

Manufacturer MIMAKI ENGINEERING CO., LTD.

2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

+81-268-64-2413

Importer / Distributor MIMAKI USA, INC.

150 Satellite Boulevard NE, suite A, Suwanee, Georgia 30024, U.S.A.

+1-678-730-0170

Emergency Telephone No. +1 866 928 0789 (within United States only, Toll free)

+1 215 207 0061

2. HAZARDS IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of 29

CFR § 1910.1200

Flammable Liquids Category 4

Serious Eye Damage/Eye Irritation Category 1

Reproductive Toxicity Category 2

GHS Label Elements

Symbols





Signal Word Danger

Hazard Statements H227 Combustible liquid.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention Obtain SDS (Safety Data Sheet) and printer's Operation Manual before

use. (P201)

Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. (P210)

Wear protective gloves, protective clothing, eye protection and face

protection. (P280)

Do not handle until all safety precautions have been read and

understood. (P202)

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

(P305+P351+P338)



Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

IF exposed or concerned: Get medical advice/ attention. (P308+P313) Immediately call a POISON CENTER/doctor/physician/first aider.

(P310)

In case of fire: Use alcohol resistant foam or normal protein foam to

extinguish. (P370+P378)

Storage Store in a well-ventilated place. Keep cool. (P403+P235)

Store locked up. (P405)

Disposal Dispose of contents/container to authorised hazardous or special

waste collection point in accordance with any local regulation. (P501)

NFPA Hazard Rating

Health 3
Flammability 2
Reactivity 0

Specific hazard Not applicable



3. COMPOSITION / INFORMATION ON INGREDIENTS

Substances or mixtures	Mixtures	
Chemical name	Contents	CAS number
Glycol ether solvent	80-90	Trade secret
Heterocyclic compound	1–10	Trade secret
Vinyl resin	1–10	Trade secret
Nickel compound	1-10	Trade secret

4. FIRST-AID MEASURES	
In case of inhalation	If fumes, aerosols or combustion products are inhaled remove from

contaminated area.

Other measures are usually unnecessary.

In case of skin contact Immediately remove all contaminated clothing, including footwear.

Flush skin and hair with running water (and soap if available).

Seek medical attention in event of irritation.

In case of eye contact Immediately hold eyelids apart and flush the eye continuously with

running water.

Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper

and lower lids.

Continue flushing until advised to stop by the Poisons Information

Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay.

Removal of contact lenses after an eye injury should only be

undertaken by skilled personnel.

In case of ingestion Immediately give a glass of water.



Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	Foam, Dry chemical powder, BCF (where regulations permit), Carbon dioxide and Water spray or fog – Large fires only.
Unsuitable extinguishing media	Cylindric water.
Specific hazards arising from the chemical	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.
Special protective equipment and precautions for fire-fighters	Alert Fire Brigade and tell them location and nature of hazard.
	Wear full body protective clothing with breathing apparatus.
	Prevent, by any means available, spillage from entering drains or water course.
	Use water delivered as a fine spray to control fire and cool adjacent area.
	Avoid spraying water onto liquid pools.
	DO NOT approach containers suspected to be hot.
	Cool fire exposed containers with water spray from a protected location.
Fire/Explosion Hazard	If safe to do so, remove containers from path of fire. Combustible.
·	Slight fire hazard when exposed to heat or flame.
	Heating may cause expansion or decomposition leading to violent rupture of containers.
	On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke.
	Mists containing combustible materials may be explosive.
	Combustion products include carbon dioxide (CO2) and other pyrolysis
	products typical of burning organic material.
	May emit poisonous fumes.
	May emit corrosive fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions See section 12



Major Spills

Safety Data Sheet

Product Identifier: SS22 Yellow SDS No. 037-S337609

First issue: 2023/09/11

Revised:

Methods and materials for containment and cleaning up

Minor Spills Remove all ignition sources.

Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes.

Control personal contact with the substance, by using protective

equipment.

Contain and absorb spill with sand, earth, inert material or vermiculite.

Wipe up

Place in a suitable, labelled container for waste disposal.

Moderate hazard.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves.

Prevent, by any means available, spillage from entering drains or water

course.

No smoking, naked lights or ignition sources.

Increase ventilation.

Stop leak if safe to do so.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.

Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal.

Wash area and prevent runoff into drains.

If contamination of drains or waterways occurs, advise emergency

services.

7. HANDLING AND STORAGE

Precautions for safe handling Safe handling

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Prevent concentration in hollows and sumps.

DO NOT enter confined spaces until atmosphere has been checked.

Avoid smoking, naked lights or ignition sources.

Avoid contact with incompatible materials.

When handling, DO NOT eat, drink or smoke.

Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling.

Work clothes should be laundered separately.

Use good occupational work practice.



Other information

Product Identifier: SS22 Yellow SDS No. 037-S337609

First issue: 2023/09/11

Revised:

Observe manufacturer's storage and handling recommendations

contained within this SDS.

Atmosphere should be regularly checked against established exposure

standards to ensure safe working conditions.

DO NOT allow clothing wet with material to stay in contact with skin.

Store in original containers.

Keep containers securely sealed.

No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for

leaks.

Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Storage incompatibility

Avoid reaction with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible	Vinyl resin	Particulates Not	5 mg/m3	Not Available	Not Available	Not Available
Exposure Limits (PELs)		Otherwise Regulated				
Table Z−1		(PNOR)- Respirable				
		fraction				
US OSHA Permissible	Vinyl resin	Particulates Not	15 mg/m3	Not Available	Not Available	Not Available
Exposure Limits (PELs)		Otherwise Regulated				
Table Z−1		(PNOR)- Total dust				
US OSHA Permissible	Vinyl resin	Inert or Nuisance Dust:	15 mg/m3 /	Not Available	Not Available	Not Available
Exposure Limits (PELs)		Total Dust	50 mppcf			
Table Z−3						
US OSHA Permissible	Vinyl resin	Inert or Nuisance Dust:	5 mg/m3 /	Not Available	Not Available	Not Available
Exposure Limits (PELs)		Respirable fraction	15 mppcf			
Table Z-3						
US NIOSH Recommended	Vinyl resin	Particulates not	Not Available	Not Available	Not Available	See Appendix
Exposure Limits (RELs)		otherwise regulated				D
US NIOSH Recommended	Nickel	Nickel metal and other	0.015 mg/m3	Not Available	Not Available	Appendix A
Exposure Limits (RELs)	compound	compounds (as Ni)				[*Note: The
						REL does not
						apply to
						Nickel
						carbonyl.]



Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Vinyl resin	120 mg/m3	1,300 mg/m3		7,900 mg/m3
Ingredient	Original IDLH		Revised IDLH	
Glycol ether solvent	Not Available		Not Available	
Heterocyclic compound	Not Available		Not Available	
Vinyl resin	Not Available		Not Available	
Nickel compound	10 mg/m3		Not Available	

Occupational Exposure Banding

Ingredient Occupational Exposure Band Rating (Occupational Exposure Band Limit
Glycol ether solvent	E	≤ 0.1 ppm
Heterocyclic compound	E	≤ 0.1 ppm

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Exposure controls

Appropriate engineering controls General exhaust is adequate under normal operating conditions. If risk

of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation

in warehouse or closed storage areas.

Individual protection measures, such as

personal protective equipment

Respiratory protection Consult with a health and safety professional for specific respirators

appropriate for your use.

Hand protection Wear chemical protective gloves, e.g. PVC.

Eye protection Safety glasses with side shields. Chemical goggles. Contact lenses

may pose a special hazard; soft contact lenses may absorb and

concentrate irritants.

Skin and body protection Wear safety footwear or safety gumboots, e.g. Rubber. Overalls.

P.V.C. apron.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State Liquid
Color Yellow
Odor Fragrant
Odor threshold Not Available
pH Not Available
Melting point Not Available
Boiling point Not Available



Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

Flash point 65.4°C

Evaporation rate Not Available Flammability(Solid,Gas) Combustible.

Flammability or explosive limits

Lower Limit Not Available
Upper Limit Not Available
Vapor pressure Not Available
Vapor density Not Available

Specific Gravity (Density) 0.9–1.0 (Relative density. Water = 1)

Solubility

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Not Available

Not Available

Not Available

2-5mPa•s

10. STABILITY AND REACTIVITY

Reactivity See section 7

Chemical stability Unstable in the presence of incompatible materials.

Product is considered stable.

Hazardous polymerisation will not occur.

Possibility of hazardous reactions See section 7

Conditions to avoid

Incompatible materials

Hazardous decomposition products

See section 7

See section 7

See section 5

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled The material is not thought to produce adverse health effects or

irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be

used in an occupational setting.

Ingestion The material has NOT been classified by EC Directives or other

classification systems as "harmful by ingestion". This is because of the

lack of corroborating animal or human evidence.

Skin Contact Skin contact is not thought to have harmful health effects (as

classified under EC Directives); the material may still produce health

damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause

inflammation of the skin on contact in some persons.

Open cuts, abraded or irritated skin should not be exposed to this

material



Product Identifier: SS22 Yellow SDS No. 037-S337609 First issue: 2023/09/11

Revised:

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye Chronic If applied to the eyes, this material causes severe eye damage. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.

Ingredient	TOXICITY	IRRITATION	
As a product	Not Available	Not Available	
Glycol ether solvent	dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation(Rat) LC50: >5.14 mg/l 4h ^[1] Oral (Rat) LD50: >2000 mg/kg ^[1]	tion(Rat) LC50: >5.14 mg/l 4h ^[1] irritating) ^[1]	
Heterocyclic compound	Dermal (rabbit) LD50: >2000 mg/kg ^[1] Oral (Rat) LD50: 300-2000 mg/kg ^[1]	Eye (rabbit): Severe Eye: adverse effect observed (irritating) [1] Skin (rabbit): mild Skin: no adverse effect observed (not irritating) [1]	
Vinyl resin	Not Available	Not Available	
Nickel compound	Inhalation(Rat) LC50: 52.222 mg/L4h ^[2] Oral (Rat) LD50: 5000 mg/kg ^[2]	Not Available	

- 1. Value obtained from Europe ECHA Registered Substances Acute toxicity
- 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS Register of Toxic Effect of chemical Substances

12. ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
As a product	Not Available	Not Available	Not Available	Not Available	Not Available
Glycol ether solvent	EC50	72h	Algae or other aquatic plants	>89.5mg/I	2
	EC50	48h	Crustacea	>93.6mg/l	2
	LC50	96h	Fish	>90.8mg/l	2
	NOEC(ECx)	504h	Crustacea	10mg/l	2
Heterocyclic compound	EC50	72h	Algae or other aquatic plants	>100mg/I	2
	EC50	48h	Crustacea	>100mg/l	2
	NOEC(ECx)	96h	Fish	>=100mg/l	2
	LC50	96h	Fish	100mg/l	2
Vinyl resin	Not Available	Not Available	Not Available	Not Available	Not Available

Page 8 of 12



Product Identifier: SS22 Yellow SDS No. 037–S337609

First issue: 2023/09/11

Revised:

Nickel compound Not Available Not Available Not Available Not Available Not Available

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances – Ecotoxicological Information – Aquatic Toxicity 4. US EPA, Ecotox database – Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) – Bioconcentration Data 7. METI (Japan) – Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Glycol ether solvent	LOW	LOW
Heterocyclic compound	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation	
Glycol ether solvent	LOW (LogKOW = 0.0093)	
Heterocyclic compound	LOW (LogKOW = -0.3135)	

Mobility in soil

Ingredient	Mobility
Glycol ether solvent	LOW (KOC = 10)
Heterocyclic compound	LOW (KOC = 15.13)

13. DISPOSAL CONSIDERATIONS

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by

country, state and/ or territory.

Each user must refer to laws operating in their area. In some areas,

certain wastes must be tracked.

Do not dump this product into sewers, on the ground or into any body

of water.

14. TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

Land transport (DOT)

Air transport (ICAO-IATA / DGR)

Sea transport (IMDG-Code / GGVSee) Transport in bulk according to Annex II

of MARPOL and the IBC code

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Not Applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture



Product Identifier: SS22 Yellow SDS No. 037-S337609

First issue: 2023/09/11

Revised:

Glycol ether solvent is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US EPCRA Section 313 Chemical List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Heterocyclic compound is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Section 12(b) - List of Chemical Substances Subject

to Export Notification Requirements

US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)

Vinyl resin is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Nickel compound is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern

List International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1:

Carcinogenic to humans

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US Clean Air Act - Hazardous Air Pollutants

US CWA (Clean Water Act) - Priority Pollutants US

US CWA (Clean Water Act) - Toxic Pollutants US

EPCRA Section 313 Chemical List

US National Toxicology Program (NTP) 15th Report Part A Known to be Human Carcinogens

US National Toxicology Program (NTP) 15th Report Part B.

Reasonably Anticipated to be a Human Carcinogen

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Page 10 of 12



Product Identifier: SS22 Yellow SDS No. 037-S337609

First issue: 2023/09/11

Revised:

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65



: WARNING

This product can expose you to chemicals including Nickel compound, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

Literature References Other data SDS of raw material

The information suggested in this Safety Data Sheet does not comprehend everything and should be adopted only as a guide. The accuracy of the information and recommendations suggested



Product Identifier: SS22 Yellow SDS No. 037-S337609

First issue: 2023/09/11

Revised:

herein are credible. However the company makes no warranty regarding such information and recommendations and disclaims all liability for reliance thereon.

Page 12 of 12