

SDS No. 037-U050561 First issue: 2008/08/28 Revised: 2019/09/05

Safety Data Sheets

1. Identification

Product Name : UV ink LF-200 Cyan

Order No. : SPC-0591C

General Use : Ink for ink jet printer

Product Description : UV Inkjet Ink SDS Number : 037-U050561

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)

+1 215 207 0061

2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Not classified

Health Hazards

Skin Corrosion / Irritation : Category 2

Eye Damage / Irritation : Category 2A

Sensitization – Skin : Category 1

Toxic to Reproduction : Category 2

Specific Target Organ Toxicity : Category 2 (skin)

(Repeated Exposure)

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements]



SDS No. 037-U050561 First issue: 2008/08/28 Revised: 2019/09/05

Safety Data Sheets

Symbol





Signal Word Warning

Hazard Statements

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure (Skin)

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe gas/mist.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash before re-use.

[Storage]

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

NFPA Rating (scale 0-4)

Health = 2

Flammability = 1

Instability = 2

Special = None





Product Name: UV ink LF-200 Cyan

SDS No. 037-U050561 First issue: 2008/08/28 Revised: 2019/09/05

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	ISOBORNYL ACRYLATE	45 - 60	5888-33-5
2	AMINE MODIFIED ACRYLATE OLIGOMER	10 - 20	Trade Secret
3	DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	5 - 15	7328-17-8
4	2,4,6-Trimethylbenzoyldiphenylphosphine oxide	5 - 15	75980-60-8
5	TETRAHYDROFURFURYL ACRYLATE	5 - 15	2399-48-6
6	SUBSTITUTED TRIAZINE	0 - 10	Trade Secret
7	1,6-HEXANEDIOL DIACRYLATE	1 - 10	13048-33-4
8	9H-Thioxanthen-9-one, 2,4-diethyl-	1 - 10	82799-44-8
9	C.I. PIGMENT BLUE 15	1 - 10	147-14-8

4. First Aid Measures

Inhalation : Remove person to fresh air. If you feel unwell, get medical attention.

Eye Contact : Immediately flush with large amounts of water. Remove contact

lenses if easy to do. Continue rinsing. Get medical attention.

Skin Contact : Immediately wash with soap and water. Remove contaminated

clothing and wash before reuse. If signs/symptoms develop,get

medical attention.

Ingestion : Rinse mouth. If you feel unwell, get medical attention.

Most important : See Section 11.1. Information on toxicological effects.

symptoms and effects,

both acute and delayed

Indication of Immediate

indication of immediate • Not

Medical Attention and

Special Treatment

Needed, If Needed

: Not applicable.



SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

5. Fire Fighting Measures

Flammable Properties : Flash point >200° F

Extinguishing Media : Use a fire fighting agent suitable for ordinary combustible material

such as water or foam to extinguish.

Special Hazards Arising

from the Chemical

: Closed containers exposed to heat from fire may build pressure and

explode.

Hazardous Combustion

: Carbon monoxide, Carbon dioxide (During Combustion)

Products

Special protective actions

for fire-fighters

: Water may not effectively extinguish fire; however, it should be used

to keep fire-exposed containers and surfaces cool and prevent

explosive rupture.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Environmental precautions

Methods and material for containment and cleaning up

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water

: Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container.



SDS No. 037-U050561 First issue: 2008/08/28 Revised: 2019/09/05

Dispose of collected material as soon as possible.

7. Handling and Storage

Precautions for Safe Handling Avoid skin contact with hot material. For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

Conditions for Safe Storage, including any Incompatibilities : Protect from sunlight. Store away from heat. Store away from oxidizing agents.

8. Exposure Controls / Personal Protection

Exposure Limit Values

: If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS No.	Agency	Limit type	Additional
				Comments
1,6-HEXANEDIOL	13048-33-4	AIHA	TWA:1 mg/m ³	Dermal
DIACRYLATE			(0.11 ppm)	Sensitizer
TETRAHYDROFURFURYL	2399-48-6	Manufacturer	TWA:0.1 ppm	
ACRYLATE		determined	(0.64mg/m ³);	
			STEL:0.3 ppm(1.91	
			mg/m³)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration



TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Exposure Controls

Occupational Exposure Controls

Appropriate

Engineering Controls

: Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

Product Name: UV ink LF-200 Cyan

SDS No. 037-U050561 First issue: 2008/08/28 Revised: 2019/09/05

Personal Protection

Respiratory

Protection



: An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates For questions about suitability for a specific application, consult with your respirator manufacturer.

Skin/Hand Protection





: Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment.

The following protective clothing material(s) are recommended:

Apron - polymer laminate



Product Name: UV ink LF-200 Cyan

SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

Eye Protection : Select and use eye/face protection to prevent contact based on the



results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

9. Physical and Chemical Properties

Appearance - Physical State : Liquid

> - Color : Cyan

Odor : Acrylate Odor,

: Not available рН

:>200° F Boiling Point / Boiling Range

Melting Point / Melting Range : Not available

Decomposition Temperature : Not available

:>200° F Flash Point

Auto ignition temperature : Not available

Flammability (Solid, Gas) : Not Applicable

Explosive Properties : Not available

Oxidizing Properties : Not available

Upper / Lower Flammability or : Not available

Explosive Limits

 $: < 10 \text{ mmHg} [@ 20 ^{\circ}\text{C}]$ Vapor Pressure

: 1.04 [Ref Std: WATER=1] Specific Gravity

: Not available Solubility

Water Solubility : Negligible

Partition Coefficient (n-octanol / Water) : Not available

: Not available Viscosity

:>1 [Ref Std: AIR=1] Vapor Density

: Not available **Evaporation Rate**

VOC : Not available



SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

10. Stability and Reactivity

Reactivity : This material may be reactive with certain agents under certain

conditions - see the remaining headings in this section.

Chemical Stability : Stable under normal conditions of use.

Possibility of Hazardous : Hazardous polymerization may occur. (Upon depletion of inhibitor or

Reactions exposure to heat)

Conditions to Avoid : Heat

Incompatible Materials : Strong oxidizing agents

Hazardous : None known.

Decomposition

Refer to section 5.2 for hazardous decomposition products during combustion

11. Toxicological Information

Inhalation : Respiratory Tract Irritation: Signs/symptoms may include cough,

sneezing, nasal discharge, headache, hoarseness, and nose and throat

pain.

Skin Contact : Skin Irritation: Signs/symptoms may include localized redness,

swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms

may include redness, swelling, blistering, and itching.

Eye Contact : Severe Eye Irritation: Signs/symptoms may include significant

redness, swelling, pain, tearing, cloudy appearance of the cornea, and

impaired vision

Ingestion : May be harmful if swallowed. Gastrointestinal Irritation:

Signs/symptoms may include abdominal pain, stomach upset, nausea,

vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated : Dermal Effects: Signs/symptoms may include redness, itching, acne,

exposure may cause or bumps on the skin.

target organ effects:



SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

Reproductive/Developme

ntal Toxicity:

: Contains a chemical or chemicals which can cause birth defects or

other reproductive harm.

12. Ecological Information

Handling is noted because it might influence the environment when

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Ecotoxicity : Please contact the address or phone number listed on the first page of

the SDS for additional chemical fate information on this material

and/or its components.

Persistence and

: Not available

Degradability

Bioaccumulation : Not available
Mobility : Not available
Other Toxicity : Not available

13. Disposal Considerations

: Comply with all USA, national and local regulations. Do not release to water. Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

<u>Do not dump this product into sewers, on the ground or into any body</u> of water.



Product Name: UV ink LF-200 Cyan

SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

EPA Hazardous Waste

: Not regulated

Number (RCRA)

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

: UN3082 **UN Number**

Shipping : Environmentally hazardous substance, liquid, n.o.s.

Name (Contains: ISOBORNYL ACRYLATE,

1.6-HEXANEDIOL DIACRYLATE)

Hazardous Class or

Division

: 9

Packing Group (PG) : IIIMarine Pollutant : Yes

Remarks : Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is

excepted from Dangerous Goods regulations.

Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.

15. Regulatory Information

U.S. Federal Regulations

SARA TitleIII : Immediate Hazard: Yes

Section 311/312 Delayed Hazard: Yes

Fire: No

Pressure: No

Reactive: No

SARA TitleIII

Section 313

Ingredient	CAS No.	%
DIETHYLENE GLYCOL ETHYL ETHER	7 990 1 7 0	F 1F
ACRYLATE (GLYCOL ETHERS)	7328-17-8	5 - 15



SDS No. 037-U050561 First issue: 2008/08/28

Revised: 2019/09/05

Safety Data Sheets

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient	CAS No.	Regulation	Status
9H-Thioxanthen-9-one, 2,4-diethyl-	82799-44-8	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

Ingredient	CAS No.	Reference
9H-Thioxanthen-9-one, 2,4-diethyl-	82799-44-8	40CFR721.9664

California Proposition

: WARNING

65



This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Inventories

: The components of this product are in compliance with the chemical notification requirements of TSCA.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.