

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

Safety Data Sheets

Identification

Product Name : Latex ink LX101 Cyan

Order No. : LX101-C-60

Ink Ver. : 1

General Use : Ink for ink jet printer

Product Description : Aqueous ink : 037-W350533 SDS Number

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)

+1 215 207 0061

Hazards Identification

[GHS Classification]

Physical Hazards

: Not classified Flammable Liquids

Health Hazards

Skin Corrosion / Irritation : Category 2 Eye Damage / Irritation : Category 2A

Specific Target Organ Toxicity : Category 3 (Respiratory tract irritation)

(Single Exposure)

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements]

Symbol





Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

Signal Word Warning

Hazard Statements

H315 Cause skin irritation

H319 Cause serious eye irritation

H335 May cause respiratory irritation.

Precautionary Statements

[Prevention]

P261 Avoid breathing gas/mist.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

NFPA Rating (scale 0-4)

Health = 2

Flammability = 1

Instability = 3

Special = None



Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Glucol ether solvents	10-20	Trade Secret
2	Alcohol solvent series	28-32	Trade Secret
3	Pigment	1-5	Trade Secret
4	Organic ingredient	1-5	Trade Secret



Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

	T	T	
5	Methyldiethanolamine	0.1-1.5	105-59-9

4. First Aid Measures

Description of first aid measures

Eye Contact : If this product comes in contact with the eyes:

Wash out immediately with fresh running water.

Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the

upper and lower lids.

Seek medical attention without delay; if pain persists or recurs seek

medical attention.

Removal of contact lenses after an eye injury should only be

undertaken by skilled personnel.

Skin Contact : If skin contact occurs:

Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available).

Seek medical attention in event of irritation.

Inhalation : If fumes or combustion products are inhaled remove from

contaminated area.

Lay patient down. Keep warm and rested.

Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask

as trained. Perform CPR if necessary.

Transport to hospital, or doctor, without delay.

Ingestion : If swallowed do NOT induce vomiting.

If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and

prevent aspiration.

Observe the patient carefully.

Never give liquid to a person showing signs of being sleepy or with

reduced awareness; i.e. becoming unconscious.

Give water to rinse out mouth, then provide liquid slowly and as

much as casualty can comfortably drink.

Seek medical advice.



SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

Safety Data Sheets

Most important symptoms and effects, both acute and delayed See Section 11.

Fire Fighting Measures

: Alcohol stable foam. Dry chemical powder. BCF (where regulations Extinguishing Media

permit). Carbon dioxide. Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility : Avoid contamination with oxidising agents i.e. nitrates, oxidising

acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting : Alert Fire Brigade and tell them location and nature of hazard.

Wear full body protective clothing with breathing apparatus.

Prevent, by any means available, spillage from entering drains or

water course.

Use water delivered as a fine spray to control fire and cool adjacent

Avoid spraying water onto liquid pools.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected

location.

If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard : Slight fire hazard when exposed to heat or flame.

Heating may cause expansion or decomposition leading to violent

rupture of containers.

On combustion, may emit toxic fumes of carbon monoxide (CO).

May emit acrid smoke.

Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.



Product Name: Latex ink LX101 Cyan SDS No. 037-W350533

First issue: 2013/06/25

Revised: 2019/10/29

Safety Data Sheets

Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

See section 8.

Environmental precautions

See section 12.

Methods and material for containment and cleaning up

Minor Spills : Slippery when spilt.

> Remove all ignition sources. Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes.

Control personal contact with the substance, by using protective

equipment.

Contain and absorb spill with sand, earth, inert material or

vermiculite. Wipe up.

Place in a suitable, labelled container for waste disposal.

Major Spills : Slippery when spilt.

Moderate hazard.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves.

Prevent, by any means available, spillage from entering drains or

water course.

No smoking, naked lights or ignition sources.

Increase ventilation.

Stop leak if safe to do so.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.

Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal.

Wash area and prevent runoff into drains.

If contamination of drains or waterways occurs, advise emergency

services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.



Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

Handling and Storage

Precautions for Safe

: Avoid all personal contact, including inhalation.

Handling

Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Prevent concentration in hollows and sumps.

DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils.

Avoid contact with incompatible materials.

When handling, DO NOT eat, drink or smoke.

Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling.

Work clothes should be laundered separately. Launder contaminated clothing before re-use.

Use good occupational work practice.

Observe manufacturer's storage and handling recommendations

contained within this SDS.

Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

DO NOT allow clothing wet with material to stay in contact with skin

Conditions for Safe

: Store in original containers.

Storage, including any

Keep containers securely sealed.

Incompatibilities

No smoking, naked lights or ignition sources.

Store in a cool, dry, well-ventilated area.

Store away from incompatible materials and foodstuff containers.

Protect containers against physical damage and check regularly for

leaks.

Observe manufacturer's storage and handling recommendations

contained within this SDS.

Are incompatible with strong acids, acid chlorides, acid anhydrides,

oxidising and reducing agents.



Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

8. Exposure Controls / Personal Protection

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
As a product	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Glucol ether solvents	Not Available	Not Available
Alcohol solvent series	Not Available	Not Available
Pigment	Not Available	Not Available
Organic ingredient	Not Available	Not Available
methyldiethanolamine	Not Available	Not Available

Exposure Controls

Occupational Exposure Controls

Appropriate : General exhaust is adequate under normal operating conditions.

Engineering Controls Local exhaust ventilation may be required in special circumstances.

> If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit

is essential to ensure adequate protection.

Provide adequate ventilation in warehouses and enclosed storage

areas.

Personal Protection

Respiratory : Consult with a health and safety professional for specific respirators

Protection appropriate for your use.



Hand Protection

: Wear chemical protective gloves, e.g. PVC.



Eye Protection

: Safety glasses with side shields.



SDS No. 037-W350533 First issue: 2013/06/25 Revised: 2019/10/29

Safety Data Sheets



Chemical goggles.

Contact lenses may pose a special hazard; soft contact lenses may

absorb and concentrate irritants.

Skin Protection : Wear appropriate chemical resistant clothing.



Wear safety footwear or safety gumboots, e.g. Rubber

9. Physical and Chemical Properties

Appearance - Physical State : Liquid

- Color : Cyan

Odor : slight

pH : 9.3-10.3

Boiling Point / Boiling Range : Not available

Melting Point / Melting Range : Not available

Melting Point / Melting Range : Not available

Decomposition Temperature : Not available

Flash Point : Not flammable

Flammability (Solid, Gas) : Not applicable

Explosive Properties : Not available

Oxidizing Properties : Not available

Specific Gravity : 1.01-1.04

Solubility : Not available

Water Solubility : Not available

Partition Coefficient (n-octanol / Water) : Not available

Viscosity : Not available

Vapor Density : Not available

Evaporation Rate : Not available

VOC : Not available

10. Stability and Reactivity

Reactivity : No reactivity hazard is expected.

Chemical Stability : Unstable in the presence of incompatible materials.

Product is considered stable.

Possibility of Hazardous : Hazardous polymerisation will not occur.



SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

Safety Data Sheets

Reactions

Conditions to Avoid : Avoid flames, sparks, and other sources of ignition. Avoid contact

with incompatible materials.

Incompatible Materials : Strong acids, acid chlorides, acid anhydrides, oxidising and reducing

agents.

: See section 5 Hazardous

Decomposition

11. Toxicological Information

Acute Toxicity : methyldiethanolamine

Dermal (rabbit) LD50: 10244 mg/kg Component Analysis -

LD50/LC50 Oral (rat) LD50: 1945 mg/kg

Information on Likely Routes of Exposure

Inhalation : Respiratory tract irritation

Ingestion : no information on significant adverse effects

Skin Contact : irritation **Eve Contact** : irritation

Immediate Effects : Skin irritation, eye irritation **Delayed Effects** : Respiratory tract irritation

Medical Conditions : No information available for the product.

Aggravated by Exposure

Irritation/Corrosivity : Skin irritation, eye irritation

Data

Respiratory : No information available for the product.

Sensitization

Dermal Sensitization : No information available for the product. Germ Cell Mutagenicity : No information available for the product.

Carcinogenicity : No data listed by ACGIH, IARC, NTP, DFG or OSHA is available for

the component(s) of this product.

Reproductive Toxicity : No information available for the product.

Specific Target Organ : Respiratory tract irritation.

Toxicity - Single

Exposure

Specific Target Organ : No target organs identified.

Toxicity - Repeated



SDS No. 037-W350533 First issue: 2013/06/25 Revised: 2019/10/29

Safety Data Sheets

Exposure

Aspiration Hazard : Not expected to be an aspiration hazard.

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity

Product: Not classified

Component Analysis - Aquatic Toxicity

Methyldiethanolamine

ENDPOINT	TEST	SPECIES	VALUE	SOURCE
	DURATION (HR)			
LC50	96	Fish	320mg/L	1
EC50	48	Crustacea	=230mg/L	1
EC50	96	Algae or other aquatic plants	=20mg/L	1
NOEC	96	Fish	=460mg/L	1

SOURCE: Extracted from 1. IUCLID Toxicity Data

Persistence and : No information available for the product.

Degradability

Bioaccumulation : No information available for the product.

Mobility : No information available for the product.

Other Toxicity : No information available for the product.

13. Disposal Considerations

: Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body

of water.

Disposal Methods : Dispose in accordance with all applicable regulations.

Component Waste : The U.S. EPA has not published waste numbers for this product's

Numbers components.

Disposal of : Empty containers may contain product residue. Dispose in

Contaminated accordance with all applicable regulations.

Packaging



Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Land transport (DOT) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

(ICAO-IATA / DGR)

Sea transport : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

(IMDG-Code / GGVSee)

Transport in bulk : Not Applicable

according to Annex II of MARPOL and the IBC

code

Marine Pollutant : NO

15. Regulatory Information

Safety, health and environmental regulations / legislation specific for the substance or mixture METHYLDIETHANOLAMINE (105-59-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No



SDS No. 037-W350533 First issue: 2013/06/25 Revised: 2019/10/29

Safety Data Sheets

Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

California Proposition 65

: WARNING:



This product can expose you to chemicals including Acetaldehyde, Formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

National Inventory Status

National Inventory	Status
Australia - AICS	Y
Canada - DSL	N
Canada - NDSL	Y
China - IECSC	N
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	N
Philippines - PICCS	N
USA - TSCA	Y

Y = All ingredients are on the inventory

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing



Product Name: Latex ink LX101 Cyan

SDS No. 037-W350533 First issue: 2013/06/25

Revised: 2019/10/29

16. Other Information

Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.